	rystal; 1-Accounting; 1-Well F	11e /
	TED STATES	FORM APPROVED
(June 1990) DEPARTMEN	T OF THE INTERIOR	Budget Bureau No. 1004-0135 Expires: March 31, 1993
BUREAU OF I	LAND MANAGEMENT	5. Lease Designation and Serial No.
CHURSY NOTICES	AND DEPORTS ON WELLS	NM-58865
	AND REPORTS ON WELLS	6. If Indian, Allottee or Tribe Name
	ill or to deepen or reentry to a different reser R PERMIT—" for such proposals	(VOII.
		7. If Unit or CA, Agreement Designation
	IN TRIPLICATE	
1. Type of Weil Oil Weil Gas Well Other		8. Well Name and No. Eagle Development No. 1
2. Name of Operator Merrion Oil & Gas Corporation		9. API Well No.
3. Address and Telephone No. P. O. Box 840, Farmington, New Mexico	87499 (505) 327-9801	10. Field and Pool, or Exploratory Area
4 Location of Well (Footage, Sec., T., R., M., or Survey Description)		Francisan Lake Mesaverd
		11. County or Parish, State
990' FNL & 2200' FEL 'Section 18, T20N, R5W		McKinley,
Section 16, 120N, RSW		New Mexico
	s) TO INDICATE NATURE OF NOTICE, R	EPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF AC	CTION
Notice of Intent	Abandonment	Change of Plans
E	Recompletion	New Construction
X Subsequent Report	Plugging Back	Non-Routine Fracturing
Final Abandonment Notice	Casing Repair	Water Shut-Off
LI FINAL ADENDONMENT NODCE	Altering Casing	Conversion to Injection
	Other	Dispose Water
	OtherOther I pertinent details, and give pertinent dates, including estimated date of all depths for all markers and zones pertinent to this work.)*	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled
give subsurface locations and measured and true vertice 13-Jun-94 MIRU A-Plus Well Service Ri Ran 120' of 1-1/4" PVC tubing Plug No. 1 mix and pump 44 s.	i pertinent details, and give pertinent dates, including estimated date of all depths for all markers and zones pertinent to this work.)* ig No. 5. Road cement equipment to location a g in 7" casing. Break circulation out 7" casing axs (15.5#) cement from 170' with good cement and cut off wellhead. Installed dry hole mark and move off location. later date.	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled and rig up. ND wellhead. g with 1 bbl water. returns out casing. ser with 10 sacks cement.
13-Jun-94 MIRU A-Plus Well Service Ri Ran 120' of 1-1/4" PVC tubing Plug No. 1 mix and pump 44 s Pull 1-1/4" tubing out of hole a	ig No. 5. Road cement equipment to location a g in 7" casing. Break circulation out 7" casing as (15.5#) cement from 170' with good cement and cut off wellhead. Installed dry hole mark and move off location. Later date.	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled and rig up. ND wellhead. If well is directionally drilled and rig up. ND wellhead. If well is directionally drilled and rig up. ND wellhead. If well is directionally drilled and rig up. ND wellhead. If well is directionally drilled and right is directionally drilled
13-Jun-94 MIRU A-Plus Well Service Ri Ran 120' of 1-1/4" PVC tubing Plug No. 1 mix and pump 44 s Pull 1-1/4" tubing out of hole a Rig down cement equipment a Will rehabilitate location at a	i pertinent details, and give pertinent dates, including estimated date of all depths for all markers and zones pertinent to this work.)* ig No. 5. Road cement equipment to location a g in 7" casing. Break circulation out 7" casing axs (15.5#) cement from 170' with good cement and cut off wellhead. Installed dry hole mark and move off location. later date.	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled and rig up. ND wellhead. g with 1 bbl water. returns out casing. ser with 10 sacks cement.
13-Jun-94 MIRU A-Plus Well Service Ri Ran 120' of 1-1/4" PVC tubing Plug No. 1 mix and pump 44 s Pull 1-1/4" tubing out of hole a Rig down cement equipment a Will rehabilitate location at a Will rehabilitate location at a	ipertinent details, and give pertinent dates, including estimated date of all depths for all markers and zones pertinent to this work.)* ig No. 5. Road cement equipment to location at g in 7" casing. Break circulation out 7" casing axs (15.5#) cement from 170' with good cement and cut off wellhead. Installed dry hole mark and move off location. later date. Operations Manager Title Operations Manager	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled and rig up. ND wellhead. If well is directionally drilled and rig up. ND wellhead. If well is directionally drilled and rig up. ND wellhead. If well is directionally drilled and right and
13-Jun-94 MIRU A-Plus Well Service Ri Ran 120' of 1-1/4" PVC tubing Plug No. 1 mix and pump 44 s Pull 1-1/4" tubing out of hole a Rig down cement equipment a Will rehabilitate location at a	ipertinent details, and give pertinent dates, including estimated date of all depths for all markers and zones pertinent to this work.)* ig No. 5. Road cement equipment to location at g in 7" casing. Break circulation out 7" casing axs (15.5#) cement from 170' with good cement and cut off wellhead. Installed dry hole mark and move off location. later date. Onerations Manager	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled and rig up. ND wellhead. g with 1 bbl water. returns out casing. ser with 10 sacks cement.
13-Jun-94 MIRU A-Plus Well Service Ri Ran 120' of 1-1/4" PVC tubing Plug No. 1 mix and pump 44 s Pull 1-1/4" tubing out of hole a Rig down cement equipment a Will rehabilitate location at a Will rehabilitate location at a (This space for Federal of State Office use) Approved by	ipertinent details, and give pertinent dates, including estimated date of all depths for all markers and zones pertinent to this work.)* ig No. 5. Road cement equipment to location at g in 7" casing. Break circulation out 7" casing axs (15.5#) cement from 170' with good cement and cut off wellhead. Installed dry hole mark and move off location. later date. Operations Manager Title Operations Manager	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled and rig up. ND wellhead. If well is directionally drilled and rig up. ND wellhead. If well is directionally drilled and rig up. ND wellhead. If well is directionally drilled and right and