

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☒ well other

2. NAME OF OPERATOR
James L. Ludwick c/o Ned Dollar, Agent

3. ADDRESS OF OPERATOR
P. O. Box 399 Aztec, NM 87410

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2310' FSL & 330' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Spud & Cement

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
JUL 02 1985

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well 6-13-85, 6PM.

Drilled 9-7/8" hole to 63'. Ran 7" 24# csng. to 63'. Cemented 35 sx Class B, 2% Cacl, circulated 4 Bbl to pit.

6-14-85 Drilled out plug w/5-1/8" bit.

6-15-85 to 6-16-85 Drilled 5-1/8" hole to 1905'. Ran 2-7/8" csng. and cemented w/200 sx Class B, 50 sx Class B w/ 2% Cacl.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ned Dollar TITLE Agent DATE July 2, 1985

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

JUL 03 1985

NMCCG

FARMINGTON RESOURCE AREA
RV 594