

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.
30-31-20995

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.
24759

7. Lease Name or Unit Agreement Name:
Fajada Wash 7

8. Well No
1

9. Pool name or Wildcat
Wildcat *Entrada*

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Synergy Operating LLC

3. Address of Operator
P.O.Box 5513, Farmington, NM 87499

4. Well Location

Unit Letter G : 2110 feet from the North line and 1630 feet from the East line
Section 7 Township 20N Range 10W NMPM McKinley County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
6266' GR, 6278' RKB

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Spud 12-1/4" surface hole @ 03:30 PM on 6/6/99. Drill 12-1/4" Surface Hole from surface to TD @ 277'. Run 9-5/8" Notched Collar as guide shoe, 6-Jts 9-5/8" 36# J-55 ST&C Csg (259.78') & land Csg @ 274' on 9-5/8" landing Jt. Establish circ, Pump 20-BBLS FW as spacer, Cmt'd 9-5/8" Csg w/ 170-sxs CL 'B' + 2% CaCl-2 + 1/4#/sx Celloflake @ 5-BPM & 100-200#, displaced wooden plug w/ 18-BBLS Wtr, plug down @ 22:45-Hrs on 6/6/99 w/ 100#, circ 18-BBLS Cmt to surf (85-sxs). Cmt steady at surface. WOC 12-Hrs. NU 11" 3M X 9-5/8" Csg Head. NU 11" 3M Shaffer LWS BOP, kill spool, & manifold Pressure Test Blind Rams, Csg & Manifold To 200# For 5-MINS, Held OK. Run 1-Jt DP w/ TIW VALVE & Test Pipe Rams, Csg, Cmt & Manifold to 200# for 5-MINS, OK, Then To 1000# for 10-MINS, HELD OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Glen O. Papp TITLE Operations Manager DATE 6/18/99

Type or print name Glen O. Papp Telephone No. 325-5449

(This space for State use)

APPROVED BY ORIGINAL SIGNED BY CHARLIE T. PERRIN TITLE DEPUTY OIL & GAS INSPECTOR, DIST. #3 DATE JUN 22 1999

Conditions of approval, if any: