

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	3

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.  
\*\*\*\*\*

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input type="checkbox"/> OTHER- <b>Wildcat</b>	7. Unit Agreement Name *****
2. Name of Operator <b>Skelly Oil Company</b>	8. Farm or Lease Name <b>Santa Fe "C"</b>
3. Address of Operator <b>P. O. Box 730 - Hobbs, New Mexico</b>	9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>"C"</b> , <b>1980</b> FEET FROM THE <b>North</b> LINE AND <b>1980</b> FEET FROM THE <b>East</b> LINE, SECTION <b>28</b> TOWNSHIP <b>18-N</b> RANGE <b>8-W</b> N.M.P.M.	10. Field and Pool, or Wildcat <b>Hospah Gallup</b>
15. Elevation (Show whether DF, RT, GR, etc.) *****	12. County <b>McKinley</b>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☒  
CHANGE PLANS ☐  
OTHER ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

**This well has been drilled to a total depth of 1933' with no commercial quantities of oil or gas being encountered in any zone. We now plan to plug and abandon this well in the following manner:**

1. Spot 30 sack cement plug from 1940' to 1799' (Hospah).
2. Spot 30 sack cement plug from 725' to 584' (Point Lookout).
3. Place 10 sack cement cap in top of 7-5/8" CD casing and install 4" steel dry hole marker.
4. All intervals not cemented will be filled with heavy mud laden fluid.

**NOTE: Mr. A. R. Kendrick gave verbal approval on June 30, 1966, for the above plugging procedure.**



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

(ORIGINAL)  
(SIGNED) **H. E. Aab**

SIGNED \_\_\_\_\_

TITLE **District Superintendent**

DATE **July 1, 1966**

APPROVED BY

*Ernest C. Aab*

TITLE

*Sup Dist TA*

DATE

**7-5-66**

CONDITIONS OF APPROVAL, IF ANY: