

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	3

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS


(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Shelly Oil Company	5. State Oil & Gas Lease No. X
3. Address of Operator P.O. Box 730 - Hobbs, New Mexico	7. Unit Agreement Name
4. Location of Well UNIT LETTER W FEET FROM THE 1960 LINE AND 1960 FEET FROM THE East LINE, SECTION 28 TOWNSHIP 18-N RANGE 8-W NMPM.	8. Farm or Lease Name Shelly Oil Co.
15. Elevation (Show whether DF, RT, GR, etc.) 6820' GR	9. Well Name Santa Fe W
16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	10. Field and Pool, or Wildcat Shelly Oil Co.
NOTICE OF INTENTION TO:	12. County McKinley
PERFORM REMEDIAL WORK <input type="checkbox"/>	
TEMPORARILY ABANDON <input type="checkbox"/>	
PULL OR ALTER CASING <input type="checkbox"/>	
OTHER <input type="checkbox"/>	
PLUG AND ABANDON <input type="checkbox"/>	
CHANGE PLANS <input type="checkbox"/>	
REMEDIAL WORK <input type="checkbox"/>	
COMMENCE DRILLING OPNS. <input type="checkbox"/>	
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>	
ALTERING CASING <input type="checkbox"/>	
PLUG AND ABANDONMENT <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well plugged and abandoned in the following manner:

1. Spotted 30-sack cement plug from 1940-1799' (Hobbs).
2. Spotted 30-sack cement plug from 725-384' (Point Lookout).
3. Spotted 10-sack cement cap in top of 7-5/8" casing and installed 4" steel dry hole marker.
4. All intervals not cemented were filled with heavy mud laden fluid.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED **(ORIGINAL SIGNED) H. E. Aab** TITLE **District Superintendent** DATE **July 11, 1966**
APPROVED BY **A. R. Beredrick** TITLE **PETROLEUM ENGINEER DIST. NO. 3** DATE **9-27-66**
CONDITIONS OF APPROVAL, IF ANY: