

F. Loc. 990/N; 1140/W Elev. 6864 DF 6-28-54 Comp. 10-18-54 TD 7658 PB 6729
 Casing 3-3/8 @ 129 W 375 Sx. Int. 5 1/2 @ 6762 W 190 Sx. Pr. @ W Sx. T. @
 Csg. Perf. Prod. Stim. See Note:

I.P. 375 8077 MCF/D After 12 Hrs. Sic. P. PSI After Days GOR Grav. 1st Del. T r a n s

TOPS	NITD	X	Well Log	TEST	DATA
Kirtland	C-102		Flat	Schd.	PC Q PW PD D ALL
Fruitland	C-103		Electric Log		
Pictured Cliffs	C-104		C-110		
Cliff House					
Menefee					
Point Lookout					
Mancos					
Tocito					
Dakota	6643				
Morrison	6770				
Entrada	7639				
Greenhorn	6452				
			Remarks		
			Note: Perf. 48 holes 6663-75		
			w. 500 G. mud acid; SOF		
			6000 G. oil, 4500# sand;		
			Perf. 104 shots 5746-5722;		
			Treated perfs. w. 250 G. mud		
			acid; SOF w. 6000 G. oil, 6000#		
			Sand; Perf. 44 holes 5721-32;		
			132 holes 5674-5707; Perf.		
			6663-75 w. 12 shots per ft.		

P Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec.
 0 Wildcat DAK Co. Rio Arriba s 15 T 23W R 5W U D Oper. Humble Lse. Jicarilla No. 1