

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved
Budget Bureau No. 42-R1424.5. LEASE DESIGNATION AND SERIAL NO.
NM 0175779

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Trans Delta Oil Co.
Lynco Oil Corporation

3. ADDRESS OF OPERATOR

7890 E. Prentice Ave. Englewood, Colorado

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1595' FNL & 800' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Hansen

8. FARM OR LEASE NAME

Hansen

9. WELL NO.

#2

10. FIELD AND POOL, OR WILDCAT

South Blanco, PC

11. SEC. T. R. M. OR BLK. AND
SURVEY OR AREA

Sec. 6, T23N, R1W

12. COUNTY OR PARISH 13. STATE

Rio Arriba New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

This well is presently producing at a non-commercial rate from casing perforations in the upper Pictured Cliffs interval 3284-3301 feet. We propose to squeeze cement the perforations from 3284-3301 feet with 100 sacks. Deepen the well from the present depth of 3340 feet and penetrate the second. Picture Cliffs sand estimated from 3380 to 3400 feet. Run a 2½" liner from total depth to 3250 feet. Fracture treat the lower Pictured Cliffs. Run 1½' tubing, Test and complete.

We plan no surface disturbance

18. I hereby certify that the foregoing is true and correct
ORIGINAL SIGNED BY
E. L. FUNDINGSLAND, JR.

SIGNED

TITLE Vice President

DATE 5-9-75

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side