	rm. 3166-5 ovenber 1983) rmc ly 9-331) DE	UNITED STATE PARTMENT OF THE BUREAU OF LAND MA	E INTERIOR	SUBMIT IN TRIPLICATI (Other lostructions og i verke side)	5. LEASE DESIGNAT	cust No. 1004-0135 cust 31, 1985 10N AND BERIAL NO. Contract 38	
	SUNDRY NOTICES AND REPORTS ON WELLS  (The not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)				6. IF INDIAN, ALLOTTEE OR TRIBE NAME  Jicarilla Apache Tribe		
1.	OIL GAB X	OTHER			7. UNIT AGREEMENT	T NAME	
2.	NAME OF OPERATOR				8. FARM OR LEASE	NAME	
	Robert L. Bay	less			AXI Apach	e H	
3.	ADDRESS OF OPERATOR		· · · · · · · · · · · · · · · · · · ·		9. Walt No.		
	P.O. Box 168, Farmington, NM 87499				6	6	
1.	LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  See also space 17 below.)  At surface 1500' FNL & 800' FEL				Ballard P	Ballard Pictured Cliffs 11. BBC., T., B., W., OR BLK. AND	
· ·					Section 6	. T23N, R5W	
31.	PERMIT NO.	15. ELEVATIONS (Sh	ow whether Dr. RT. G	R. etc.)	12. COUNTY OR PAR	ISH 13. STATE	
		6786	5' GL 6794	' KB	Rio Arriba	a NM	
16.		neck Appropriate Box To	Indicate Nature		Other Data		
	TEST WATER SHUT-OFF	PULL OR ALTER CASIN					
	FRACTURE TREAT	MULTIPLE COMPLETE	<b>"</b>	WATER SHUT-OFF FRACTURE TREATMENT	REPAIRIN		
	SHOOT OF ACIDIZE	ABANDON*	:	SBOOTING OR ACIDIZING	<del></del>	CABING	
	REPAIR WELL	CHANGE PLANS		(Other) Plug and Aba	l ABANDON	MENT* X	
	(Other)				ts of multiple completi pletion Report and Log	on on Well	
	See Attached Daily	Report	H M	E 1 7 E 10 2 6 1992	<b>9</b> 2 1919		
	• •		Di	ST	DEC 16 AMIO: 47 FARMINGTON.N.M	RECEIVED	
 K,	1 hereby certify that to for	Liab	roved as to plug ility under bond ace restoration i	ging of the well bore. is retained until s completed.	<del></del>		
	SIGNED Kevin-H. McCo	Mynl,	Petrole	um Engineer	DATE12	2-15-92	
	(This space for Federal or S	oute omce use)					
	APPROVED BYCONDITIONS OF APPROVA		TITLE		A P P R O	∨ <del>E D</del>	
		*See	Instructions on R	leverse Side	DEC 21.1		

## PLUG AND ABANDON REPORT

## ROBERT L. BAYLESS

## AXI APACHE H #6 SENE SEC 6, T23N R5W RIO ARRIBA COUNTY, NEW MEXICO

- 12-8-92 Move in and rig up A+ Well Service. Lay blowlines and blow down well. Nipple down wellhead, nipple up BOP. Trip 69 jts (2225 ft.) of 1 1/4" IJ tubing out of hole. Shut down for the night.
- 12-9-92 Trip in hole with 1 1/4" tubing to 2238' spot 50 sx (59 ft3) plug of class B cement with 2% Cacl from 2238' to 1808' pull tubing to 1612' wait on cement to set tag plug at 1898' pull tubing up to 1878' spot 50 sx (59 ft3) plug of class B cement with 2% Cacl from 1878' to 1448' pull tubing up to 1431' mix 27 bbls of 8.5 #/gal, 36 viscosity mud and spot from 1431' to 283' pull and lay down tubing up to 303' mix 40 sx (47 ft³) plug of class B cement with 2% Cacl from 303' to the surface finish pulling and laying down tubing dig out and cutoff wellhead install dry hole marker with 10 sx of cement rig down rig job complete.

## PLUG SUMMARY:

Plug #1 1898 - 2238 50 sx 59 ft<sup>3</sup> Plug #2 1448 - 1878 50 sx 59 ft<sup>3</sup> Plug #3 surf - 303 40 sx 47 ft<sup>3</sup>

note: BLM employee Kevin Snyder witnessed plugging operations.