

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 03993

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

D. E. FLORANCE

3. ADDRESS OF OPERATOR

3352 S. VERBENA COURT, DENVER, COLORADO 80222

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

790' SL & 1450' WL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

7508 KB

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

F

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

SO BLANCO PC

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

8-23N-1W

12. COUNTY OR PARISH

13. STATE

RIO ARriba

NEW MEXICO

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 10-24-70.

Cemented 8-5/8" casing at 110' 75 sacks. Cement circulated. WOC 8 hours. Pressure tested casing to 600 psi for 30 minutes. No decrease in pressure. Drilled 6-3/4" hole to total depth 3300; Ran IES log on 10-27-70. Cemented 4-1/2" casing at 3300' with 125 sacks on 10-28-70. Perforated Pictured Cliffs 3230-34, 3236-44 and 3248-52 with 2 hole per foot. Sand water fracture treated perforations 3230 - 3252 down casing with 30,000 # 10-20 sand and 40,030 gallons of water. Breakdown pressure 2600 psi. Average treating pressure 1600 psi. Instant SI 500 psi. Shut in overnight. Ran 1-1/4" tubing to 3237' and swabbed well in on 11-1-70. Well flowing at 4:00 P.M. Flowed 24 hours and shut in gauge.



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side