## UNITED STATES

UNITED STATES	5. LEASE (
DEPARTMENT OF THE INTERIOR	N00-14-C-20-5603 4 6 5 5
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME SERVED TO BE SERVED T
1. oil 🔀 gas 🗇	8. FARM OR LEASE NAME of Single of S
Well Well with the second seco	9. WELL NO. 20 5 1 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
2. NAME OF OPERATOR Dietrich Exploration Co.	10. FIELD OR WILDCAT NAME 및 호텔
3. ADDRESS OF OPERATOR Denver, Co. 80202 602 Midland Saving Bldg.,444 Seventeenth St	11. SEC., T., R., M., OR BLK, AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA পুরুতি চুল্লি জুলির জুলির Sec 8, T23N, R7W গুলির
below.) AT SURFACE: 480' FNL & 1680' FWL	12. COUNTY OR PARISH 13. STATE 3
AT TOP PROD. INTERVAL: Same	Rio Arriba
AT TOTAL DEPTH: Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO. Seria and the seri
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	7054 GL, 7067 KDB ਕੋ ਡਾਵਰੋਟ
TEST WATER SHUT-OFF T	d reports to provide the copies to the copie
FRACTURE TREAT	nd repo of copies
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
MULTIPLE COMPLETE	Znoitstego   bestgede en change of bestgede en change of bonter bonter en change of bo
CHANGE ZONES	Si op Si on Si op
ABANDON*	្ធ អាវិទិស្ស ស្វារ
(other)	znoituntzi moitstego llev betgesse to edmun eiti b moit bariere phasi neibal t moti bluorie tra- to sant bra- ede art bra- to sant bra- ede art bra- to sant bra-
AT DECORURE PROPOSED OF COMPLETED OPERATIONS (OLd the state	<u> </u>
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinent	rectionally drilled, give subsurface locations and
- · · · · · · · · · · · · · · · · · · ·	
Rotary Tools were moved in and rigged up. A	12%" note was spudded and delited
to 275'. Ran 8 5/8" 20# surface casing to 27	I' KB. Cemented With Zau-SK. Class
"B" cement. Plug down at 2145 hrs. 1-3-78. (	rement circulated to mith in p. of
top of hole.	of all care and al
11 14 6 10 1 m 1 1 1 1 m 2 1 4 1 2 1 7 2 m 4	
Wait on cement 12 hrs, test bop and drill out with 7 7/8 bits a sign	
	<b>ĕ</b> ≶ <b>₽ ₹ ₹ ₹ ₹ ₹ ₹</b>
	2 X Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z
,	1 3 5 5 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	न्य विकास के विकास के अपने के
	5 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 -
Subsurface Safety Valve: Manu. and TypeN/A	Set 6 5 7 5 6 Ft.
18. I hereby certify that the foregoing is true and correct	and an
SIGNED WILL OLD CHANGE TITLE Agent	DATE 4-4-78 59 889
John Alexander/	19 3 4 6 B 20 1 0
(This space for Federal or State office	Bid Take the second of the letter of the let
APPROVED BY TITLE	DATE DATE DATE
CONDITIONS OF APPROVAL, IF ANY:	
	meil boses boses boses
	5 <u>5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 </u>