

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR  
KENAI OIL AND GAS INC.
3. ADDRESS OF OPERATOR  
717 17th St., Ste. 2000, Denver, CO 80202
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1650' FSL - 790' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☐  
☐  
☐  
☐  
☐  
☐  
☒  
☐

5. LEASE  
NM-23051
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
NONE
7. UNIT AGREEMENT NAME  
West Lybrook Unit
8. FARM OR LEASE NAME  
FEDERAL - 7
9. WELL NO.  
#13
10. FIELD OR WILDCAT NAME  
Lybrook (Extension)-Gallup
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 7, T23N-R7W
12. COUNTY OR PARISH  
Rio Arriba
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7119' GL (graded); 7129' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Set Speedy-line bridge plug @ 5530' and completed well by perforating Lower Gallup, 5462-70' and Upper Gallup 5343-49' and acidizing and fracing each zone separately. Swab and flowing tests before recovery of all load water indicate the well will produce 10 to 15 bbls oil per day, plus 200 to 300 MCF per day; a commerical completion in the Gallup.


Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED George B. Judd Manager - Drilling and Production DATE 6/

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:



ACCEPTED FOR RECORD

JUN 19 1980

FARMINGTON DISTRICT

\*See Instructions on Reverse Side

BY [Signature]