UNITED STATES

DEPARTMENT OF THE INTERIOR	Contract 78 6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla		
GEOLOGICAL SURVEY			
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME		
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME		
1. oil gas well other	AXI "P" Apache F		
2. NAME OF OPERATOR	7		
Robert L. Bayless	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Ballard Pic. Cliffs		
P.O. Box 1541, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OF		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec. 11, T23N, R5W		
AT SURFACE: 1630' FNL & 1690' FEL	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL: same	Rio Arriba N.M.		
AT TOTAL DEPTH: same	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
	6794 ¹ GL		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF			
FRACTURE TREAT	i de la companya del companya de la companya del companya de la co		
SHOOT OR ACIDIZE			
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9–330.)		
	2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2		
CHANGE ZONES			
A DANIDON!			
ABANDON Amend Sundry cement report of 04-05-82			

5. LEASE

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Please amend Sundry Notice of 04-05-82 for operations reported for 04-02-82. All is correct except the last paragraph which should read as follows:

Rigged up National Cementers. Cemented casing with 200 sacks Class "B" cement with 2% econofil (11.8#/gal.) tailed by 50 sacks Class "B" cement with 2% CaCl (15.6#/gal); good circulation throughout job. Circulated approximately 10 sacks cement; plug did not bump; plug down at 10:30 p.m. 04-02-82.

Subsurface Safety Valve: Manu. and Type			Set @	. Ft.
18. I hereby certify that the foregoing is true and correct			A	
SIGNED LOS TITLE	Operator	DATE	April 6, 1982	
To but Day This space for I				
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:		DATE _		
			ACCEPTED FOR RECORD	

*See Instructions on Reverse Side

7F7 07 1982