

Form 5-231
(May 1983)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on the
reverse side)

Field Approval
Bureau Survey No. 40-R142
3. LEASE DESIGNATION AND SERIAL NO.

SF-078272

6. IF INDIAN, ADDRESS OF TRIBAL NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☒ OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

BCO, Inc.

3. ADDRESS OF OPERATOR

135 Grant Ave. Santa Fe, New Mexico 87501

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

600' FNL 660' FEL Sec. 3 T23N R7W

RECEIVED

MAY 26 1982

7. UNIT ACREMENT NAME

8. FARM OR LEASE NAME

Dunn

9. WELL NO.

10

10. FIELD AND NAME OF WILDMAT
Lybrook Gallup & Undesignated Graneros

11. SEC. T23N R7W OR BLM AND SURVEY OR AREA

Sec 3 T23N R7W

14. PERMIT NO.

15. ELEVATIONS (Show weather st. or other survey)

GR 6890

12. COUNTY OR PARISH 13. STATE

Rio Arriba N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT

REPAIR WELL

CHANGE PLANS

(Other) Drilling Progress -- Spud Report XX

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROMISED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting at proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and append to this work.)

5-23-82 Notified Sue with Minerals Management Answering Service that we intended to cement surface pipe on this well between 6:00 and 12:00 P.M. on 5-23-82.

5-23-82 Drilled 12 1/4" hole and ran 284' 24 # 8 5/8 K55 surface pipe. Landed pipe at 294'. Cemented with 200 sacks Class B 3% CaCl cement, with 1/4 # floccell per sack. Circulated 10 barrels cement. Plug down 10:00 P.M.

5-24-82 Ready to drill out surface at 9:00 A.M.



18. I hereby certify that the foregoing is true and correct

SIGNED Harry R. Boyl

TITLE President

ACCEPTED FOR RECORD

DATE 5-25-82

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

FARMINGTON DISTRICT

BY

Smm

VMOCCL