

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form 5-331
Bureau of Land Management
U.S. Department of the Interior

3. LEASE DESIGNATION AND AREA

SF-078272

6. IF INDIAN, ALLOTTEE OR TRIBAL

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

BCO, Inc.

3. ADDRESS OF OPERATOR

135 Grant Ave. Santa Fe, New Mexico 87501

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FNL 390' FEL Sec. 3 T23N R7W

RECEIVED

JUN 07 1982

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dunn

9. WELL NO.

11

10. FIELD AND FORM OF WILDCAT
Lybrook Gallup & Unders
nated Graneros

11. SEC., T., R., M. OR BLK. AND
SURVEY OR AREA

Sec 3 T23N R7W

14. PERMIT NO.

15. ELEVATIONS (Show whether DT, RT, CR, etc.)

GR 6953

12. COUNTY OR PARISH 13. STATE

Rio Arriba N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

RELL OR ALTER CASINO

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

☐
☐
☐
☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

REACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Drilling Progress - Spud Report ☒

REPAIRING WELL

ALTERING CASINO

ABANDONMENT

☐
☐
☐
☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and pertinent to this work.)

6-3-82 Notified Carrie Peterson with the Farmington Minerals Management Office we intended to cement surface pipe on this well between 6:00 PM and 12:00 PM today 6-3-82.

6-3-82 Spudded and drilled 12 1/4" hole. Ran 286' 24" 8 5/8 K55 surface pipe. Landed pipe at 296. Cemented with 200 sacks Class B 3% CaCl cement, with 1/4# floccell per sack. Circulated 10 barrels cement. Plug down 12:15 AM 6-4-82.

6-4-82 Waiting on cement at 6:00 AM.



RECEIVED FOR RECORD

JUN 10 1982

FILED

BY SMH

18. I hereby certify that the foregoing is true and correct

SIGNED Harry R. Blythe

TITLE President

DATE 6-4-82

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

NMOCC