I LUTTET COU

## **UNITED STATES** DEPARTMENT OF THE INTERIOR

**BUREAU OF LAND MANAGEMENT** 

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

6. If Indian, Allottee or Tribe Name

NW 41721

SUNDRY	NOTICES	AND	REPO	DRTS	ON	WELLS
--------	---------	-----	------	------	----	-------

Use "APPLICATION FO	TEB 6 PM 3: 43			
SUBMIT	FARMINGTON, NM			
1. Type of Well				
Well Gas Other	8. Well Name and No.			
2. Name of Operator	Gallo White #1			
Dugan Production Corp.	9. API Well No.			
3. Address and Telephone No.	30 039 22944			
P.O. Box 420, Farmington, NM	10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey D	Counselors Gallup/DK			
1660' FSL & 2000'FEL (NW/4 S	11. County or Parish, State			
1660' FSL & 2000'FEL (NW/4 S Unit J, Sec. 14, T23N, R6W, N	Rio Arriba, NM			
OHIC U, Sec. 14, 125N, ROW, N	rum	KIO HIIDA, WI		
12. CHECK APPROPRIATE BOX(	s) TO INDICATE NATURE OF NOTICE, R	EPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION			
X Notice of Intent	X Abandonment	Change of Plans		
_	Recompletion	New Construction		
Subsequent Report	Plugging Back FEB 2 2 1994	Non-Routine Fracturing		
	Casing Repair	Water Shut-Off		
Final Abandonment Notice	Altering Casing)   CON	Conversion to Injection		
	Other	Dispose Water		
	DIST. 3	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)		
	pertinent details, and give pertinent dates, including estimated date of all draths for all markers and zones pertinent to this work.)	starting any proposed work. If well is directionally drilled,		

While attempting to return this well to production, the casing was found to be parted at 1698'. Attempts to recover a retrievable bridge plug at 5098' were unsuccessful and the plug will be left in the hole. Plan to plug well as follows by verbal approval from Steve Mason, 2-15-94:

- 1. Spot 50' Class B cement plug on top of bridge plug @ 5098'.
- 2. Spot 100' Class B cement plug across Mesa Verde top @ 3532'.
- 3. Spot Class B cement plug from 1321' to 2018' to cover Pictured Cliffs, Fruitland, and Ojo Alamo tops, plug the parted casing at 1698'.
- 4. Spot surface plug 0' to 420' with Class B cement.
- 5. Attempt to pump down bradenhead. If rate can be established, fill with cement.

Signed Alexander	Title Operations Manager	Date 2/16/94
(This space for Federal or State office use)  Approved by Conditions of approval, if any:	Title	Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side -

DISTRICT MANAGER