

SUNDRY NOTICES AND REPORTS ON WELLS

1. oil ☐ gas ☐ other Dual Completion

below.)
AT SURFACE: 1980' FSL and 660' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

(other) Production Casing Cement

SUBSEQUENT REPORT OF

NATURE OF NOTICE, 15. ELEVATION
Gr. 706

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

Report change

RECEIVED
MAY 9 1983

15. ELEVATIONS (SHOW DF, KDB, AND WD)
Gr. 7063'

04/11/83 Ran 7308' of new 5½" K-55 17lb/ft casing.

Equipment	Depth	Cement
1. Guide Shoe	7308'	
2. Float Collar	7270' w/625 sks (768.75 ft ³)	50/50 Poz 2% Gel 6 lbs Kolite
3. Stage Collar	5210' w/620 sks (762.50 ft ³)	50/50 Poz 2% Gel 6 lbs Kolite
4. Stage Collar	3110' w/400 sks (492 ft ³)	50/50 Poz 2% Gel 6 lbs Kolite
5.	Tail in 100 sks (118ft ³)	Class B 2% CaCl ₂ W.O.C.

SIGNED W.B. Martin TITLE Operator DATE May 6, 1983

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 13 1983

FARMINGTON DISTRICT

PM

NMCCC