

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other

2. NAME OF OPERATOR

Chace Oil Company, Inc.

3. ADDRESS OF OPERATOR

313 Washington, SE, Albuquerque, NM 87108

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

Unit 'C', 710' FNL & 2015' FWL

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:

5. LEASE

Tribal Contract #71

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla Tribal Contract #71

9. WELL NO.

M-12

10. FIELD OR WILDCAT NAME

S. Lindrith Gallup Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 10, T23N, R4W

12. COUNTY OR PARISH 13. STATE

Rio Arriba

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

7305' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

AUG 29 1983

OIL CON. DIV.

DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/12/83: Ran 188 joints, plus a short joint, of 4½" 11.6 lb/ft, N-80 casing, set @ 7615' KB. Guide shoe @ 7614'. Float collar @ 7574'. D. V. tool @ 3203'. Short joint from 6029-6050'. Cement baskets @ 6962', 6095', 5705', 5217', 4888', 2523'. 1st stage: Pumped 20 bbls flochek-21. Cemented 1st stage with 1200 sks (1716 CF) 50/50 pozmix, 2% gel, 6¼ lb/sk Gilsonite, 6 lb/sk salt. Plug down @ 6:25 P. M. Opened. D. V. tool. Circulated upper stage 3 hours. Cemented 2nd stage. Pumped 20 bbls mud flush. Cemented with 425 sks, (990 CF) 65/35 pozmix, 12% gel, 6¼ lb/sk Gilsonite. Tailed in with 50 sks (59 CF) Class B neat. Plug down @ 10:13 P. M. Circulated 2 bbls cement to surface.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

D. W. Mills

TITLE

President

DATE

August 15, 1983

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 25 1983

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA
FARMINGTON, NEW MEXICO

BY

smm

NMOCC