Form 3160-5 (November 1994)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or reenter an abandoned well., Use Form 3160-3 (APD) for such proposals.

FORM APPROVED OMB No. 1004-0135 Expires "1ly 31, 1996

5. Lease Serial No.

ŀ	N	М	S	F	-0	7	8	2	7	2
---	---	---	---	---	----	---	---	---	---	---

6	If Indian,	Allottee	or Tribe	Name

aparidorica won.	, 000, 0,,,, 0,,,, 0,,,,		<b>21</b> (1715				
SUBMIT IN TRIPL	ICATE Other instru	ctions on	reverse	ં ે side	À	7. If Unit or CA	/Agreement, Name and/or No.
1. Type of Well			LED				
X Oil Well Gas Well	Other		- 1 '			8. Well Name a	
2. Name of Operator					<i>i</i> [	Campos 4 #	
Elm Ridge Resources, Inc.						9. API Well No	
3a. Address		3b. Phone N	No. (include a	area codé)	L	30-039-2679	
PO Box 189 Farmington, NM	87499	505-632-3	3476				ol, or Exploratory Area
4. Location of Well (Footage, Sec., T., R	., M., or Survey Description)					Lybrook Gal	
450' FNL & 1905' FEL						11. County or Pa	rish, State
Sec. 4-T23N-R7W				•		Rio Arriba, I	New Mexico
12. CHECK APPROPRIATE BOX(I	ES) TO INDICATE NATURE	OF NOTICE	, REPORT,	OR OT	HER DA	ГА	
TYPE OF SUBMISSION	TYPE OF ACTION						
Notice of Intent	Acidize Alter Casing	Deepen Fracture		Re	clamation	tart/Resume)	Water Shut-Off Well Integrity Tother Drilling
Subsequent Report	Casing Repair	L	nstruction I Abandon		complete mporarily	Ahandon	X Other Dilling
C Si tal Lamad Nation	Change Plans Convert to Injection	Plug Bac			ater Dispos		
Final Abandonment Notice  13. Describe Proposed or Completed Operat	, U				_		pproximate duration thereof.
Spud well on 12-7-01 @ 2:30 KB. Cemented with 315 sx C Circulate 20 bbls cement to st Resolution Induction Log and @ 2654' KB. Cemented first .5% Halad, 9-5# Gilsonite, 1/4 cement to surface. Cement 2 "H", .5% Halad, 9-5# Gilsonite bbl cement to surface. Rig do	PM. Drilled 12-1/4 hole lass "B" cement, 3% cc, urface. Drilled 7-7/8 to 5 Spectral Density Log F stage w/650 sx 65/35 PC I# Flocele, 1% CC. Burn and stage w/540 sx 65/35 e, 1/4# Flocele,1% CC.	1/2# cellofl 987'KB. TC Ran 143-joi DZ 6% gel, Ip plug to 2 IPOZ, 6% ( Drop plug a	lake. Disj D reached nts 4-1/2 1/4# Floc 2000 PSI a Gel, 1/4# and close	place w I @ 5:3 I, 11.6# sele, 10 and ope Flocele stage t	oth 23.3 0 PM or J-55 ca # Gilsor en stage e, 10# C ool w/4	is dois water 1 12-19-01. asing- set @ nite, 1% CC e tool. Circu Silsonite, 1%	Ran Halliburton High 6045' KB. Stage tool s and 150 sx Class "H", late 4 hrs and 32 bbls CC and 50 sx Class
bel comment to carrie as a sign							•
- 45 15 1 5 1 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	00 4040 0002 4550 1960	1				:-	••
Certified Return Receipt # 70		, 					
14. I hereby certify that the foregoing is	true and correct	l Title				÷	
Name (Printed/Typed)	Grubelnik , k	Tide			Product	ion Technici	ian
Signature A DIA	Wu hoh	Date			Janu	ary 17, 2002	
7000	THIS SPAC	E FOR FEDE	RAL OR ST	ATE US	ŧ.		
Approved by	·	T	itle			Date	
Conditions of approval, if any, are attached certify that the applicant holds legal or ed which would entitle the applicant to cond	quitable title to those rights in the s net operations thereon.	subject lease	Office				
Title 18 U.S.C. Section 1001, makes it a fraudulent statements or representations a	crime for any person knowingly an	d willfully to ma on.	ake to any de	partment o	or agency o	f the United State	s any false, inclitious or

MH