

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Dryhole		5. LEASE DESIGNATION AND SERIAL NO. Tribal #422
2. NAME OF OPERATOR Woods Petroleum Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla
3. ADDRESS OF OPERATOR P. O. Box 18667, Oklahoma City, Oklahoma, 73118		7. UNIT AGREEMENT NAME -
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FWL & 660' FSL (SW S'W)		8. FARM OR LEASE NAME Jicarilla
14. PERMIT NO. -		9. WELL NO. H-1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6832' KB, 6818' GL		10. FIELD AND POOL, OR WILDCAT Wildcat
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 11-22N-5W
		12. COUNTY OR PARISH Sandoval
		13. STATE New Mexico

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION NO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐


ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We drilled a 13-3/4" hole to 270', set 269' 9-5/8" surface casing, and cemented to surface. We reached a total depth of 6,365', driller's measurement, on 12-11-71. Evaluation using Compensated Formation Density Log, Dual Induction-Laterolog, Gamma Ray-Neutron, and drill stem tests showed an absence of prospective pay sands. Permission to plug and abandon was obtained from U.S.G.S. Plugs will be placed as follows:

43 sack plug	6370-6150'
39 sack plug	4700-4600'
27 sack plug	5750-5650'
10 sack plug	3200-3250'
Bridge plug @	1450'
220 sack plug	1420- surface.



18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

Vice President

DATE

December 20, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side