

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports on Wells

91 JUN 21 PM 2:41

1. Type of Well
GAS

5. Lease Number

Jic. Cont. 417

6. If Indian, All or

Tribe Name

Jic. Apache

7. Unit Agreement Name

2. Name of Operator

JUL 09 1991

Meridian Oil Inc.

OIL CON. DIV.

3. Address & Phone No. of Operator

Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number

Jicarilla O #1

9. API Well No.

4. Location of Well, Footage, Sec, T, R, M.

SWSW

Sec. 10, T-22-N, R-3-W, NMPM

10. Field and Pool

W. Lindrith Gallup Dakota

11. County and State

Sandoval County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☒ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut Off

☐ Altering Casing

☐ Conversion to Injection

☐ Other

13. Describe Proposed or Completed Operations

06-12-91 MOL&RU. TOOH w/266 rods. ND WH. NU BOP. SDFN.
06-13-91 Pump 40 BW. TOOH w/221 jts tbgs. TIH to 6730'. SD for weekend.
06-17-91 Spot 40 sx Class "B" neat cmt across Dakota 6383-6736'. Pull up to 6000'. WOC. TIH, tag plug @ 6353'. Load hole w/9% 50 vis mud, pull tbgs to 5380'. Spot 25 sx Class "B" cmt 5380-5162'. Pull tbgs up to 3930'. SDFN.
06-18-91 PT csg 500#, pump into leak. TOOH w/tbgs. TIH w/FBP, found hole in csg 2290-2410'. Run pkr to 3663' & set. Perf 2 squeeze holes @ 3936'. Cmt w/50 sx Class "B" neat cmt. Displace 6 bbl. cmt out squeeze holes. Left 5.5 bbl. in csg. Pull pkt to 2991', reverse circ clean. Reset pkr. SDFN.
06-19-91 Move pkr to 2928 & set. Perf 2 squeeze holes @ 3240'. Tag lower plug @ 3696'. Cmt w/50 sx Class "B" neat cmt, circ out squeeze holes @ 3040'. Left 4.5 bbls. in csg. TOC @ 3040'. TOOH. w/pkr. Shot 2 squeeze holes @ 2446'. TIH w/cmt ret @ 2227'. Cmt w/175 sx Class "B" neat cmt below ret. Spot 75 sx Class "B" neat on top of ret. Shot 2 holes @ 1612'. Spot 50 sx Class "B" neat cmt. Pull tbgs to 324'. SI backside. Cmt w/20 sx Class "B" neat cmt @ 324'. TOOH w/tbgs. Cmt w/25 sx Class "B" neat cmt pumped down bradenhead. Set dry hole marker.
06-20-91 Released rig.

14. I hereby certify that the foregoing is true and correct

Signed Deputy State Field Title Regulatory Affairs Date 6-20-91

(This space for Federal or State office use)

APPROVED BY

NMOC

TITLE

DATE