

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side.)

Form approved
Budget Bureau No. 1004-0135
Expires August 31, 1985

6. LEASE DESIGNATION AND AERIAL NO.

NM16582, ~~NM17105~~, NM125808

7. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back for a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

SEP 9 1985

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

JN OIL AND GAS

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

3. ADDRESS OF OPERATOR

550 N. 31st Street, Suite 220 Billings, Montana 59101

4. LOCATION OF WELL (Report location clearly and to accordance with any state requirements.
See also space 17 below.)
At surface

2035' FNL & 1105' FEL SENE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Natani

9. WELL NO.

20

10. FIELD AND POOL, OR WILDCAT

Rusty Chacra

11. SEC., T., R., M., OR ECL. AND
SURVEY OR AREA

Sec. 34-T22N-R6W

12. ELEVATION (SHOW WHETHER DE, BT, GR, ETC.)

30-043-20641

7020' KB

Sandoval

N.M.

13. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PAUL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

COMPLETION

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones per-
tinent to this work.) *

1. This well has 4½" casing set at 2144' and cemented to surface.

2. Plan to plug and abandon as follows:

1. Set 10sx cement plug from 1750' to 1850'. (Chacra)

2. Set 10sx cement plug from 1550' to 1450'. (Pictured Cliffs & Fruitland)

3. Set 10sx cement plug from 810' to 910'. (Ojo Alamo)

4. Cement abandonment marker at surface. 50'

3. Have minimum of 9.2#/gal. mud in hole between plugs.

4. Location has been recontoured and reseeded per Sundry Notice filed November 10, 1985.

RECEIVED

SEP 12 1985

OIL CON. DIV.

DIST. 3

APPROVED

8/29/85

AS AMENDED

SEP 10 1985

AREA MANAGER
FARMINGTON RESOURCE AREA

18. I hereby certify that the foregoing is true and correct

SIGNED

Don Rimmer

TITLE

Petroleum Engineer

This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCC