•							
Form 9–331 Dec. 1973	5 MMS, Fmn 2 Wexpro	l File	Form Approved Budget Bureau No. 42-R1424				
	UNITED STATES	5. LEASE	3 Julia 3 No. 42 - R1424				
DEF	PARTMENT OF THE INTERIOR	NM 16	046				
	GEOLOGICAL SURVEY	6. IF INDIA	N, ALLOTTEE OR TRIBE NAME				
		-	<u></u>				
	OTICES AND REPORTS ON WELLS		REEMENT NAME				
(Do not use this form for reservoir, Use Form 9-3)	or proposals to drill or to deepen or plug back to a differen 31–C for such proposals.)	t	<u> 1920 (</u>				
1. oil gas	S 1440	_ 8. FARM OF	R LEASE NAME				
well wel	other	9. WELL NO					
2. NAME OF OPER		1					
	PRODUCTION CORP.	10. FIELD OF	R WILDCAT NAME				
3. ADDRESS OF O		Undes	ignated PC				
4 1004TION 05 W	ox 208, Farmington, NM 87401	11. SEC., T.,	11. SEC., T., R., M., OR BLK. AND SURVEY OR				
below.)	ELL (REPORT LOCATION CLEARLY. See space 17	AREA					
AT SURFACE:	790' FNL - 1850' FWL	Sec 21	Sec 21 T21N R4W 12. COUNTY OR PARISH 13. STATE Sandoval NM				
AT TOP PROD.							
AT TOTAL DEPTI	· · · · · · · · · · · · · · · · · · ·	14. API NO.	'al NM				
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA							
REPORT, OR OT	HER DATA	15. ELEVATIO	ONS (SHOW DF, KDB, AND WD)				
REQUEST FOR APPR	ROVAL TO: SUBSEQUENT REPORT OF:	7 42'	GL; RKB = GL				
TEST WATER SHUT-	OFF D RECEIVE	ED					
FRACTURE TREAT SHOOT OR ACIDIZE		1					
REPAIR WELL		2					
PULL OR ALTER CAS		(NOTE: Report	results of multip@commetion or cope				
MULTIPLE COMPLETI CHANGE ZONES	U. S. GEOLOGICAL S	URVEY	C. So &				
ABANDON*	FARMINGTON, N.	M	0/0 190				
(other)	XX Spud & surfac	e casing	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \				
17 DESCRIBE PROPE		₹					
including estimat measured and tru	OSED OR COMPLETED OPERATIONS (Clearly stated and control of starting any proposed work. If well is does need to be used to be starting and cones pertinents.)	e all pertinent de irectionally drilled t to this work.)*	etails, and give perting tes, d, give subsurface locations and				
9-23-82	MI & RU Morrow Drilling Co. rig.	: Spudded 8	-3 Mil hold at 10-00				
	p.m. 9-22-82. Drilled to 100'.	Ran 3 its.	. 7" N ∩ _320# _854				
	ST&C "B" Condition casing. T.E.	97.37' set	at 98' GL.				
			<u>- 경우왕</u> 경우왕씨				

Cemented with 35 sk class "B" plus 2% CaCl (41.3 cf). P.O.B. at 11:00 p.m. 9-22-82. Cement circulated. +W.O.C.

Subsurface Safety Valv	ve: Man y and Typ	e			Set @ _		E+
18. I hereby certify tha					50, 6		_ [.
SIGNED OM	Thomas A.	Dugan Pe	etroleum Engin	eer _{bate} _	9-23-82		
APPROVED BYCONDITIONS OF APPROV		(This space for F	ederal or State office u	se)	ACCEPTED	, FOR RECO	IRD
CONDITIONS OF AFFROY	AL, IF ANT.					•	

SEP 2 (199)

FARMING TO HOLE

BY