

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

(Other instructions on reverse side)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER Re-enter

2. NAME OF OPERATOR J.N.C. Resources

3. ADDRESS OF OPERATOR 6506 S. Lewis Suite 162 Tulsa, OK 74136

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

5. LEASE DESIGNATION AND SERIAL NO. N.M. N.M. 29186

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME Anthony #2

9. WELL NO. 2

10. FIELD AND POOL OR WILDCAT wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 9 T16N R2W

12. COUNTY OR PARISH Sandara 13. STATE N.M.

14. PERMIT NO. 671016 AM 9:20

15. ELEVATIONS (Show whether DF, RT, CR, etc.) G. 6245

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

17. DISCOVERED OR RECOMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed well. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

18. I hereby certify that the foregoing is true and correct

SIGNED John A. Oakley TITLE Agent DATE 11/14/87

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

- 11/1 Cut off dry hole marker. Drill out. 176' cement in top of hole
210' cement from 900 - 1100. 300' 1610 - 1910.
Press test casing @ 2000' 1500# 5 min. held.
- 13 Drilled cement from 2100 - 2200.
Drilled cement from 2500 - 2700. Tested casing @
2200' to 2000# 20 min. held.
- 14 Cleaned out hole to 2764. Acidized with 2000 gals
2 1/2% H.C.L. flush with 37 Bbls 2 1/2% H.C.L. 16.5 BPM I.S.P. 100#

RECEIVED
NOV 17 1987
OIL CON. DIV.
DIST. 3

*See Instructions on Reverse Side