

6 BLM 1 Robinson 1 File
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 14970

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

B.R.'s Stars

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Undesignated Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 17, T21N, R3W, NMPM

12. COUNTY OR PARISH 13. STATE

Sandoval

NM

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

DUGAN PRODUCTION CORP.

3. ADDRESS OF OPERATOR

P O Box 208, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

330' FSL - 500' FEL

RECEIVED

MAY 20 1987

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7125' GL; 7137' RKB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETION ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOT OR ACIDIZE ☐

ABANDON* ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT* ☒

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) ☐

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plugged and abandoned the subject well on 5-15-87 as follows:

1. Spotted cement plug 5470' - 5021' (60 c.f. - 51 sx).
2. Spotted cement plug 3384' - 3284' (13 c.f. - 11.5 sx).
3. Spotted cement plug 2773' - 2673' (13 c.f. - 11.5 sx).
4. Spotted cement plug 1908' - 1808' (13 c.f. - 11.5 sx).
5. Spotted cement plug 262-162' (13 c.f. - 11.5 sx).
6. Spotted cement plug 100' - surface (13 c.f. - 11.5 sx).

Spotted plug 1699-1380
(37' - 31.5 sx)
Per Jim Jacobs 5/20/87

Note: 9.2# mud or heavier was placed between plugs.
All cement plugs are class "B" neat.

Equipment will be removed and restoration done at a later date.

Approved to be used for
Liability under the
Surface Reclamation Act of 1976

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE Geologist

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE 5-19-87

MAY 20 1987

DATE

AREA MANAGER
FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side

NMOCC