

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATION*
(Other instructions on re-
verse side)

Project Bureau No. 1004-0135
Expires August 31, 1985
6. LEASE DESIGNATION AND SERIAL NO.

NM-39532

7. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ Drilling

2. NAME OF OPERATOR
Champlin Petroleum Company

3. ADDRESS OF OPERATOR
P. O. Box 1257, Englewood, CO 80150

4. LOCATION OF WELL (Report location clearly and in accordance with State requirements. See also space 17 below.)
At surface

SESW (930' FSL & 1980' FWL)

MAY 03 1984

BUREAU OF LAND MANAGEMENT
EARMINGTON RESOURCE AREA

14. PERMIT NO.
Approved 2-16-84

15. ELEVATIONS (Show whether DV, RT, OM, etc.)
6,866' GL

8. FARM OR LEASE NAME
Federal 24-11

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Mancos

11. SEC., T., R., W., OR S.W., AND
SUBST. OR AREA

Section 11-T20N-R3W

12. COUNTY OR PARISH
Sandoval

13. STATE
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Operations

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 12 1/4" hole at 1:45 p.m. 4-24-84, drilled to 541'. Ran 13 jts. 9-5/8" K-55, 36# ST&C casing, shoe @ 536'. Cemented w/350 sx Class B cement with 1/4#/sx Flocele and 2% CaCl₂. Plug down @ 1:45 a.m. Circulated cement to surface. WOC 8 hours. Drilled 8-3/4" hole to 2,050'.

Present operation: Drilling.

RECEIVED

MAY 10 1984

"OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED R. A. Scott

TITLE Sr. Engineering Aide DATE 4-30-84

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

MAY 03 1984

EARMINGTON RESOURCE AREA

RV

Smm

NMOCC
*See Instructions on Reverse Side