

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR
Robert L. Bayless

3. ADDRESS OF OPERATOR
P.O. Box 1541, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1850' FSL & 1850' FEL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Spud & set surface csg.

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

APR 26 1984

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

5. LEASE

Contract 390

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Tribe

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla 390

9. WELL NO.

#2

10. FIELD OR WILDCAT NAME

Ballard Pic. Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 26, T23N, R4W

12. COUNTY OR PARISH

Sandoval

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

7128' GL 7133' RKB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-24-84 Drilling @ 900', wt. 8.9, visc. 32, W.L. 7

Spud well @ 11:00 a.m. 4-23-84. Drill 126' of 9-7/8" surface hole. Ran 123' of 7" 20#/ft. J-55 used surface casing and set at 125' RKB. Rigged up Cementers Inc. Cemented surface casing with 40 sacks (98 ft³) Class B cement with 2% CaCl₂. Good circulation throughout job. Circulated cement to the surface. Plug down at 2:15 p.m. 4-23-84. WOC 8 hours.

Drill 900' 6 1/4" hole in 7 hours. Deviation @ 1/4° at 700'.

4-25-84 Tripping @ 1970'. Wt. 9.0, Visc. 31, W.L. 10. Deviation @ 1970' = 1/2°

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kevin H. McLeod TITLE Petroleum Engineer DATE 4-25-84

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

APR 27 1984

OIL CON. DIV.
DIST. 3

*See Instructions on Reverse Side

NMOCC

APR 26 1984

FARMINGTON RESOURCE AREA

BY Smm