

APR 11 1956

(Orig. Sgd.) P. T. McGRATH  
DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Indian Agency \_\_\_\_\_

Allottee \_\_\_\_\_

Lease No. Trabala 73

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____	X
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____	
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____	
NOTICE OF INTENTION TO ABANDON WELL _____		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

\_\_\_\_\_ 1925

Well No. \_\_\_\_\_ is located \_\_\_\_\_ ft. from  $\begin{Bmatrix} N \\ S \end{Bmatrix}$  line and \_\_\_\_\_ ft. from  $\begin{Bmatrix} E \\ W \end{Bmatrix}$  line of sec. \_\_\_\_\_

_____	_____	_____	_____
(1/4 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)
Wildcat	Sandoval		New Mexico
(Field)	(County or Subdivision)		(State or Territory)

The elevation of the derrick floor above sea level is 710 ft. O.L., 7112 D.F.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 55.47 feet of 9 5/8 inch 40# surface casing at ground level, 45.47 feet below Kelly Bushing, circulated to surface with 50 sacks cement. Drilled 3 3/4 inch hole to 1625 feet. Drilled 7 7/8 inch to total depth of 2636 feet. Run 2620.49 feet of 5 1/2 inch 15 1/2 pound J55 casing to depth of 2630 feet below Kelly Bushing, cemented with 75 sacks, pressured plug with 1,000 pounds. Perforated casing with 9/16 inch bullets as follows: 12 shots 2582 to 2600; 24 shots 2572 to 2578. 32 shots 2557 to 2565. 16 shots 2551 to 2555; 24 shots 2544 to 2550; 24 shots 2536 to 2542. Fractured well with 30,000 gallons water, 25,000 pounds of sand. Well made brackish water after fracturing, 17,000 ppm chlorides. Prepare to find free point in casing. Pull approximately 1800 feet. Place cement plug in top of casing, and second cement plug from 250 feet up into surface casing. Set marker and restore location to original condition.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company CASHWELL SILVER  
Address 321 Simons Building  
Albuquerque  
New Mexico

By Cashwell  
Title Operator

