

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in **TRIPLICATE** to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON Perforating & Treating (Other)	X

May 20, 1955
(Date)

Farmington, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Great Western Drilling Company
(Company or Operator)

Chaco Unit
(Lease)

Great Western Drilling Company, Well No. 2 in the SW $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 16
(Contractor)

T. 23N, R. 8W, NMPM., Wildcat Pool, San Juan County.

The Dates of this work were as follows: May 15-18, 1955

Notice of intention to do the work (was) (~~1955~~) submitted on Form C-102 on May 10, 19 55
(Cross out incorrect words)

and approval of the proposed plan (was) (~~1955~~) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The water in the casing was displaced with oil and the casing was perforated with 232 Kone-Shots and 290 bullets as follows May 15-16-17, 1955.

4921-4951 - 4 Kone-Shots and 5 bullets per foot.
4986-4997 - 4 Kone-Shots and 5 bullets per foot.
5029-5039 - 4 Kone-Shots and 5 bullets per foot.
5062-5069 - 4 Kone-Shots and 5 bullets per foot.

No production gauges were taken after perforating.

The perforations were washed with 500 gallons of mud and the well was sand-frao'd with 433 bbls. of oil and 30,000 pounds of sand May 18, 1955. The load oil will be pumped out. The total load and flush oil used was 1078 bbls.



Witnessed by Jack Page Great Western Drilling Company Div. Prod. Supt.
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION
Original Signed Emery C. Arnold
(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name Jack Page
Position Division Production Superintendent
Representing Great Western Drilling Company
Address 211 1/2 West Main, Farmington, N. M.

Oil and Gas Inspector Dist. #3. MAY 23 1955
(Title) (Date)

OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received <u>4</u>		
DISTRIBUTION		
	NO. FURNISHED	
Operator	<u>1</u>	
Sanita Fu	<u>1</u>	
Proration Office		
State Land Office		
U. S. G. S.	<u>1</u>	
Transporter		
File		<input checked="" type="checkbox"/>