

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe, New Mexico

Lease No. ST 07562

Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 1 is located 990 ft. from N line and 990 ft. from W line of sec. 19  
23 E. 11 N. U.S.P.M.  
 (Twp.) (Range) (Meridian)  
Stratton New Mexico  
 (Field) (County or Subdivision) (State or Territory)

The elevation of the Well Bottom above sea level is 4314 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Status: Total depth: 5220'  
 Surface casing: 8 5/8" cement at 228'.  
 Hole size: 7 7/8" from 228' to total depth.

Abandonment Work:

- (a) With open end drill pipe hung at 5200' plugged with 75 sacks construction cement  
 (b) With open end drill pipe hung at 5008' plugged with 80 sacks construction cement  
 Found top of cement at 4790'. Cleaned out to 5020'.
- Made drill stem test #5. (results previously reported on Form 9-331a dated July 18, 1956).
- With open end drill pipe hung at 4950' plugged with 50 sacks cement (4800-4950)  
 With open end drill pipe hung at 4080' plugged with 90 sacks cement (3850-4080)  
 With open end drill pipe hung at 3150' plugged with 50 sacks cement (3000-3150)  
 With open end drill pipe hung at 2350' plugged with 70 sacks cement (2150-2350)  
 With open end drill pipe hung at 200' plugged with 20 sacks cement (180-200)


Company Hell Oil Company

Address 33 Richards Street

alt Lake City 1, Utah

By B. W. Shepard

Title Exploitation Engineer



(OVER)

4. Capped with a 10 sack cement plug, installed marker and officially abandoned July 15, 1956.

