

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0555915

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Foshay

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

9-T23N-R13W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5936 GR

12. COUNTY OR PARISH

San Juan

13. STATE

N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Operations Report

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

November 15, 1971 - Spudded surface hole on 11/13/71 and drilled to 525'. Set 13 3/8" OD H-40 New Casing at 525' KB and cased w/ 400 sks. Foamix + 150 sks. reg. Plug down at 2:00 PM on 11/14/71 w/ good returns.

November 22, 1971 - DST No. 1 (4420-4470) ISI 60" (2347#). Open 60" (736-682#)

FSI 120" (2320#). Rec. 1209' MC water, 2894' MOCN, 60' drlg. mud

November 23, 1971 - Drilled to 4873', w/ hole deviated to 12". Deviations as follows: 4000'-1 1/2", 4200'-5", 4400'-13", 4500'-12", 4580'-13", 4600'-12". Plugged back from 4873' to 4111' w/ 150 sks. reg. cement.

November 26, 1971 - Drlg. at 4200'; Survey 3"


November 27, 1971 - Drlg. at 4303'; Survey 4267-3", 4295-2 1/2"

November 28, 1971 - Drlg. at 4466'; Survey 4336-2", 4370-1 3/4, 4400-1 3/4"

November 29, 1971 - Drlg. at 4650'; Survey 1 1/4" at 4650'

November 30, 1971 - Drlg. at 4827'; Survey 1 1/4" at 4807'

December 1, 1971 - Drilling Ahead



RECEIVED

JAN 5 1972

U.S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray A. Smith

TITLE

Regional Production Manager

DATE

12/29/71

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

