

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE\*  
(Other instructions on reverse side)

Form approved  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM555915-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

None

7. UNIT AGREEMENT NAME

None

8. FARM OR LEASE NAME

Foshay

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

S9, T23N, R13W, N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER Wildcat

2. NAME OF OPERATOR

Apache Corporation

3. ADDRESS OF OPERATOR

4815 S. Harvard Ave., Tulsa, Oklahoma 74101

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)

At surface 1980' fr N line, 660' fr W line,  
Section 9, Township 23 North, Range 13 West,  
N.M.P.M.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5936' Gr.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Well was temporarily abandoned by BJ Service on January 22, 1972, per instructions Mr. P. T. McGrath, USGS, Farmington, under the directions of Mr. Dale Luhman and Mr. Tom Sprinkle, engineers for Apache Corp. The following Cement plugs (50/50 Pozmix) were set with drill pipe:

9460-9803'	(T.D.)--55 sx.
8900-9100'	-----69 sx.
7100-7300'	-----69 sx.
5650-5800'	-----52 sx.
5200-5350'	-----52 sx.
4630-4930'	-----103 sx. (this plug set across the base of the 8 5/8" csg. @ 4780')

The 8 5/8" csg. remains in hole awaiting salvage, is full of 9.8 lb. mud and is capped at the surface by a steel plate welded over the well head. (All data derived from Apache Corp. well reports.)

18. I hereby certify that the foregoing is true and correct

SIGNED

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY