Forty 9-331 (M: y 1963)	UNITED STATES SUBMIT IN TRIPLACE  DEPARTMENT OF THE INTERIOR verse side:  GEOLOGICAL SURVEY	
(Do	SUNDRY NOTICES AND REPORTS ON WELLS not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)	
OIL WELL	GAS WELL X OTHER	
	OPERATOR Benson Mineral Group, Inc.	4
	of OPERATOR 1726 Champa St., #600, Denver, _CQ80202	
Sec also At surfa		
	1570' FSL and 840' FEL, Sec. 41422N-1882	

	NM-7011		
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
	7. UNIT AGREEMENT NAME		
74.	8. FARM OR LEASE NAME Federal 4-22-8 9. WELL NO.		
	1 10. FIELD AND POOL, OR WILDCAT Wildcat		
	11. SEC., T., B., M., OR BLK. AND SUBVEY OR ABEA  Sec. 4-T22N-R8W		
	12. COUNTY OB PARISH   13. STATE		

San Juan

Form approved. Budget Bureau No. 42-R1424.

NM

5. LEASE DESIGNATION AND BERIAL NO.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

15. ELEVATION (Show whether DF, RT, GR, etc.)

6032 GR

U. S. Challman . Thorogy

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF PULL OR ALTER CASING	WATER SHUT-OFF REPAIRING WELL	
FRACTURE TREAT MULTIPLE COMPLETE	FRACTURE TREATMENT ALTERING CASING	
SHOOT OR ACIDIZE ABANDON*	SHOOTING OR ACIDIZING ABANDONMENT*	
REPAIR WELL CHANGE PLANS	(Other)	
(Other)	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Benson Mineral Group, Inc. intends to plug and abandon this well as follows:

See attached modifications.

- 1. Spot cement plug 30' to surface and 1300' 1830'
- 2. Erect PxA marker

16.

3. Clean up and re-seed location



SIGNED And . Lawrence and		DATE 6-28-82
James S. Jameson	TITLE	DATE
(This space for Federal Paris of the Be		
APPROVED BY APPROVE	U TITLE	DATE
JUL 0 6 1982AS	AMENDED NMOCC	
Fur JAMES F. SIMS		
DISTRICT ENGINEER	*See Instructions on Reverse Side	

## U. S. GEOLOGICAL SURVEY Drawer 600 Farmington, New Mexico 87499-00600

Attachment to Notice of

Intention to Abandon

Re: Permanent Abandonment

Well: 1 Federal 4-22-8

## CONDITIONS OF APPROVAL

Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal Leases."

- The Farmington office (telephone (505) 325-4572) is to be notified in sufficient time for a representative to witness all plugging operations.
- Blowout prevention equipment is required.
- In addition to normal filling of pits and cleanup of location, additional surface restoration work  $\underline{may}$  be required, i.e. ripping of pad and/or access road, reseeding, etc. We have asked the Bureau of Land Management for the surface restoration requirements for this well and we should be able to furnish you these requirements within 30 days. After plugging the well and before making final clean-up, you should contact this office unless you have already been advised as to what additional surface restoration work is required.
- The following modifications to your plugging program are to be made (when
  - a) Spot cement plug from P.B.T.D. to 1400' to cover perforations and top of La Ventana.
    b) Spot cement plug from 1117' to 1017' to cover top of Pictured Cliffs.

  - c) Spot cement plug from 980' to 880' to cover top of Fruitland.
  - d) Spot cement plug from 440' to 340' to cover top of Ojo Alamo.
  - e) Spot cement plug from 150' to surface cover surface casing shee.

Office Hours: 7:30 A.M. to 4:15 P.M.