

5 BLM, Fmn 2 Celsius 1 File

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR  
DUGAN PRODUCTION CORP.

3. ADDRESS OF OPERATOR  
P O Box 208, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 790' FSL - 790' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT TO:

☐ **RECEIVED**  
**MAY 9 1983**  
**U. S. GEOLOGICAL SURVEY**  
**FARMINGTON, N. M.**  
☒ 2-7/8" casing

5. LEASE  
NM 16762

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Witty

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Wildcat Chacra

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 12 T23N R10W

12. COUNTY OR PARISH | 13. STATE  
San Juan | NM

14. APN NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6682' GL

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-5-83 Rigged up and ran 55 jts. 2-7/8" O.D., 6.5#, EUE 10V tubing for casing. T.E. 1691.56' set at 1690' G.L. Cemented with 75 sx 2% Lodense with 1/4# cello flake per sk followed by 100 sx class "B" neat. (Total cement slurry 272 cu.ft.) Reciprocated pipe while cementing. Good circulation throughout. Circulated approx. 1 1/2 bbls. cement to surface. P.O.B. at 3:30 p.m. 5-4-83.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Geologist DATE 5-6-83

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 11 1983

NMOCC