

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ Drilling

2. NAME OF OPERATOR
Champlin Petroleum Company

3. ADDRESS OF OPERATOR
P. O. Box 1257, Englewood, CO 80150

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) NE SW
AT SURFACE: 1726.7' FWL & 1855.1' FSL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other) Operations Report

SUBSEQUENT REPORT OF:

5. LEASE

Nm 36352

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 23-14

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 14 T22N R10W

12. COUNTY OR PARISH 13. STATE

San Juan New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6306' CL, 6321' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OCT 21 1983

OIL CON. DIV.
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 12-1/4" hole at 12:30 P.M. 9-25-83. Drilled to 430'. Ran 10 jts. (408') 9-5/8", 36#, K-55 casing. Shoe at 420' K.B., float collar at 382' K.B. Cemented with 275 sx (325 C.F.) Type "B" cement with 2% CaCl₂, 1/4#/sack Celloflake. Good returns. Cement to surface. Plug down at 4:00 A.M. 9-26-83. W.O.C. 8 hours. Tested BOP, blind rams, and manifold to 1200#, held O.K. Tested casing and pipe rams to 1200#, held O.K.

Drilled 8-3/4" hole 430-1,080'.

Present Operation: Drilling.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ramona J. Rhoden nmz Sr. Engineering
Ramona J. Rhoden

(This space for Federal or State office use)

ACCEPTED FOR RECORD
DATE 9-27-83

OCT 19 1983

APPROVED BY _____
CONDITIONS OF APPROVAL IF ANY:

TITLE _____

DATE _____

FARMINGTON RESOURCE AREA

BY Smm

NMOCC