

RY SMm

DUGAN PRODUCTION CORP.

December Dream #1

Page 3

1-7-84

Finished laying down drill pipe. Rigged up and ran 130 jts. 4½" O.D. 10.5#, K-55, 8 Rd, ST&C casing. T.E. 5942' set at 5936' RKB. Dowell cemented first stage with 10 bbls. mud flush followed by 350 sx 50-50 poz w/ 2% gel & ¼# cello flake per sk followed by 100 class "B" with ¼# cello flake per sk. (Total cement slurry first stage = 563 cf.) Bumped plug with 1500 psi. Held OK. Dropped opening bomb. Opened stage tool at 3786'. Circulated with rig pump 3½ hrs. Dowell cemented 2nd stage with 10 bbls. mud flush followed by 800 sx 65-35 plus 12% gel and ¼# cello flake per sk. followed by 50 sx 50-50 poz plus 2% gel and ¼# cello flake per sk. (Total cement slurry 2nd stage 1832 cf) Good circulation throughout both stages. Reciprocated casing OK on first stage. Circ. all mud flush and 3 bbls. contaminated cement on 2nd stage. Closed stage tool with 2500 psi. Held OK. Job complete at 6:00 p.m. 1-6-84. Nippled down BOP. Set 4½" casing slips. Cut off casing. Released rig at 8:00 p.m. 1-6-84.

RECEIVED
JAN 13 1984
OIL CON. DIV.
DIST. 3