

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.

LH-1896

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> WELL GAS <input checked="" type="checkbox"/> WELL OTHER-	7. Unit Agreement Name
2. Name of Operator DUGAN PRODUCTION CORP.	8. Farm or Lease Name Wit's End
3. Address of Operator P O Box 208, Farmington, NM 87499	9. Well No. 5
4. Location of Well UNIT LETTER <u>M</u> <u>790</u> FEET FROM THE <u>South</u> LINE AND <u>790</u> FEET FROM THE <u>West</u> LINE, SECTION <u>2</u> TOWNSHIP <u>23N</u> RANGE <u>10W</u> NMPM.	10. Field and Pool, or Wildcat Undes. Pictured Cliffs
15. Elevation (Show whether DF, RT, GR, etc.) 6722' GL	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <u>Spud, Surface Casing & Pressure Test</u> <input checked="" type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moved in and rigged up Morrow Drilling Company. Spudded an 8-3/4" hole at 11:30 A.M. 10-9-86. Drilled to 100' GL. Ran 3 jts. 7" OD, 20#, 8 Rd, "B" condition casing (T.E. 97.08') set @ 99' G.L. Cemented with 35 sacks class "B" cement (41.3 cf). P.O.B. @ 3:30 P.M. 10-9-86. Circulated good cement to surface. W.O.C. 16½ hours. Pressure tested B.O.P. and surface casing 500 psi for 30 minutes before drilling out - held OK.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jim L. Jacobs TITLE Geologist DATE 10-13-86APPROVED BY ORIGINAL SIGNED BY ERNIE BUSCHTITLE DEPUTY OIL & GAS INSPECTOR, DIST. #3DATE OCT 14 1986

CONDITIONS OF APPROVAL, IF ANY: