Form 3160-5 (November 1983)1 - SLC	UNITED STATES SUBM	File IT IN TRIPLICATE*	Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985
(Formerly 9-331) UEPARIMENT OF THE INTERIOR verse adde)			5. LEASE DESIGNATION AND SERIAL NO.
BUREA	U OF LAND MANAGEMENT		NOO-C-14-20-7310
(Do not use this form for propos Use "APPLICA	ICES AND REPORTS ON WEL sais to drill or to deepen or plug back to a diff. ATION FOR PERMIT—" for such proposals.)	erent reservoir.	Navajo Allottee
I. OIL X GAB OTHER			7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	Profesional Control (Control Control C	MEXICO	S. FARM OR LEASE NAME
DUGAN PRODUCTION CORP.			Squaw Valley
3. ADDRESS OF OPERATOR). WELL NO.
P.O. Box 420, Farmington, NM 87499 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*			2
See also space 17 below.) At surface			O. FIELD AND POOL, OR WILDCAT
810' FSL & 730' FWL			South Bisti Gallup Ext. 11. SEC., T., R., M., OR ELK. AND SURVEY OR AREA
·			Sec. 4, T23N, R10W, NMPM
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)		2. COUNTY OR PARISH 13. STATE
	6547' GL; 6559' KB		San Juan NM
Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data			
SUBBEQUENT REPORT OF:			
FRACTURE TREAT		SHUT-OFF	REPAIRING WELL
		UBE TREATMENT	ALTERING CABING ABANDONMENT®
<u> </u>	HANGE PLANS (Other	T.D., casing	
Other) UIL CON.	DIV.	NOTE: Report results of Completion or Recompletion	multiple completion on Well
DESCRIBE PROPOSED OR COMPLETIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* T.D. 4640 reached on 3-15-90. Conditioned hole. P.O.H. and ran			
IES and CDL lodrill pipe ar 10.5#, J-55, Cemented 1st cello-flake Reciprocated cementing. Macalculated di Dropped openi with rig pump pump - circu Cemented 2nd cello-flake/s Total cement pumped 10 bbl full mud return cement to sur - held OK. Joset 4-1/2" cas 6:00 A.M. 3-16	ogs by H.L.S. T.I.H. and collars. Rigged up 8 Rd, ST&C casing (T.E. stage* with 235 sx 50-per sk (total slurry casing OK while cementing aximum cementing pressures placement and did not not not bomb and opened stage for 2-1/2 hrs. (Note: lated out 3 to 4 bbls stage* with 700 sx 6 r sk followed by 50 sx 5 k (total cement slurry slurry used in both stage ships, cut off 4-1/6-90. Sing slips, cut off 4-1/6-90.	d conditioned and ran 107 4641.95') sering and stage to 3-16-90. Note that sering and sering	mud. Laid down jts. 4-1/2" OD, et at 4637' RKB. 2% gel and 1/4# = 298 cu.ft.). nud returns while Went 3 bbls over Float held OK. 10'. Circulated ulating with rig m first stage). 2% gel and 1/4# = 1611 cu.ft.). cu.ft. *Note: oth stages. Had eximately 15 bbls ol with 2500 psi ippled down BOP,
Jim L. Jacobs	TITLE		MK-26 1990
On a space for Federal or State office	use)		211
ACEROVED BY			iof, PATE
CONDITIONS OF APPROVAL, IF AND	Γ:	Min	Constant of the constant of th
	zaid se a		100 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1