

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1450' FNL & 1550' FWL (SE/4 NW/4)
Unit F, Sec. 20, T22N, R8W, NMPM

5. Lease Designation and Serial No.

NM 57445

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Zappa #1

9. API Well No.

30 045 29062

10. Field and Pool, or Exploratory Area

W/C Bisti Chacra (96031)

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other T.D., casing & cement

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 1220' reached on 4-4-94. Circulate hole. Made 20' hole TD 1220'. Short trip & circulate. Laid down drill pipe. Schlumberger ran IES & CDL logs. TIH with 38 jts. 2-7/8" OD NU 6.4# 10 Rd tubing used for casing landed at 1217', float collar at 1185'. Circulate hole. Pump 10 bbls water. Cement with 60 sx lodense w/1/4# celloflake and tail with 130 sx neat w/1/4# celloflake (276 cu.ft. total slurry). Displace with 7 bbls water. Shut in. Circulate 7 bbls cement. Note: hydrotested all 2-7/8" tubing used for casing to 3500 psi.

RECEIVED
APR 13 1994

RECEIVED
APR 13 1994

14. I hereby certify that the foregoing is true and correct

Signed

Jim Jacobs

Title

Vice-President

Date

4/6/94

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOC

FARMINGTON DISTRICT OFFICE

3V