Other

Final Abandonment Notice

Form 3160-5 (Sume 1990)

1. Type of Well X Vel

## UNITED STATES

	M WIN	715
Budget Bu	neen No.	1004-013
		.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Ezairea	: March	51. <b>199</b> 3

DEPARTMENT	OF	THE	INTERIOR
RUPFAU OF LA	ND	MAN	IAGEMEN

5.	Lease	Designat	ion prin	i Serial	No.

SUNDRY NOTICES A	ID REPORT	is on wells
------------------	-----------	-------------

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

NM 36952 6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

F10 J0 #6

... is i

December 1	9. API Well No.	
Dugan Production Co	orp.	30 045 29288
3. Address and Telephone No.	ngton, NM 87499 (505) 325-1821	
P.O. Box 420, Farmi	10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  1990' FSL & 2230' FWL (NE/4 SW/4)  Unit K, Sec. 1, T23N, R11W		South Bisti Gallup
		San Juan County, NM
12. CHECK APPROPRIA	TE BOX(s) TO INDICATE NATURE OF NOTIC	E, REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE C	OF ACTION
Notice of latent	Abandonment	Change of Plans
_ [D]	ECENVER Recompletion	New Construction

13. Describe Proposed or Completed Operations (Clearly State all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

X Other TD, casing & cement

T.D. 4650' reached on 4/2/97. TIH with 104 jts. 43" 10.5# J-55 casing landed @ 4650', float collar @ 4610', stage tool @ 3483'. Pump 10 bbls mud flush. Cement 1st stage w/300 sx 50/50/2 w/1 celloflake. (slurry 1st stage=381 cf). Plug down @ 0230 hrs 4/3/97. Opened stage tool. Circulate 3 hrs. Pump 10 bbls mud flush, 10 bbls water with red dye. Cement 2nd stage w/590 sx 65/35/12 w/\fracelloflake & tail with 50 sx 50/50/2 w/\fracelloflake (slurry 2nd stage=1367 cf). Total cement slurry both stages=1748 cf. Plug down at 0745 hrs 4/3/97. Had good circulation throughout both stages. Circulate 35 bbls cement. Nipple down BOP, set slips & cut off casing.

Conditions of approval, if any:		ACCEPTED FOR HECORD			
Approved by	Ticle		Date		-
(This space for Federal or State office use)					
Signed Cary Print	Title	Operations Manager	Date		=
14. I hereby certify that the foregoing is the and correct		O marking Managor	_	4/4/97	
<u> </u>					=

Tide 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictious or fraudulent statements or representations as to any matter within its jurisdiction.