Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	FORM APPROVED	
	Budget Bureau No. 1004-0135	
RECEINED	Expires: March 31, 1993	
	Lease Designation and Serial No.	
PPV.	Contract 36	

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservor Use "APPLICATION FOR PERMIT—" for such proposals	Jicarilla Apache
SUBMIT IN TRIPLICATE	Unit or CA. Agreement Designation
Type of Well Oil Well X Well Other Name of Operator Conoco, Inc. Address and Telephone No. 3817 N.W. Expressway, Oklahoma City OK 73112 (405) 948-3100 Location of Well (Footage, Sec., T., R., M., or Survey Description) Unit Letter E, 1606' FNL & 928' FWL Sec. 22-24N-5W CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REI	8. Well Name and No. N.E. Haynes No. 5 9. API Well No. 30-039-05099-00 10. Field and Pool, or Exploratory Area Otero Gallup/Dakota 11. County or Parish. State Rio Arriba NM PORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTI	
Notice of Intent DEGEVED Abandonment Recompletion Plugging Back Casing Repair	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.

- Set a CIBP at 6721' (50' above the top Dakota perforation). Dump bail 4 sacks of cement 1. on top of plug.
- Set a CTDP at 5593' (50' above the top Gallup perforation). Dump bail 4 sacks of cement 2. on top of plug.
- Isolate the Pictured Cliffs and Ojo Alamo formations by perforating the casing 50' below the top of each horizon, setting a cement retainer and cementing. The Ojo Alamo will be 3. isolated from the deep horizons by perforating and cementing the casing 50' below the zone. An attempt will be made, however, to circulate cement from the Pictured Cliffs to cover the Oja Alamo formation to reduce perforating and cementing costs.
- Spot cement plugs across the Mesaverde, Chacra, Pictured Cliffs, and Ojo Alamo formations 4. inside the casing.
- Set cement retainer at 500' and circulate cement through (casing leak) holes at 560' to 5. surface.
- Pull out of retainer and circulate cement to surface inside the 5-1/2" production casing. 6.
- Erect P&A marker and clean and restore the locations to its natural state. 7.

STE ATTROHED FOR CUMPITIONS OF APPROVAL

		APPROVED
14. I hereby certify that the foregoing is true and correct		AFFRYSEL,
Signed James Jakes	Sr. Oil & Gas Assistant	AS AMENDED
(This space for Federal or State office use)		JUL 03 19 91
Approved by	Title	1 1338
Conditions of approval, if any:		
56		AREA MANAGER
	the and willfully to make to any department or agency of the	United States any false fictitions or fraudulent stateme

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the Unit or representations as to any matter within its jurisdiction.

GENERAL INSTRUCTIONS

structions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

his form is designed for submitting proposals to perform certain well opertions, and reports of such operations when completed, as indicated, on ederal and Indian lands pursuant to applicable Federal law and regulaons, and, if approved or accepted by any State, on all lands in such State, oursuant to applicable State law and regulations. Any necessary special in-

SPECIFIC INSTRUCTIONS

zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and the depth to top of any left in the hole; method of closing to of well; the abandonment.

lem 4—If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

hem 13—Proposals to abandon a well and subsequent reports of abandon-ment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include and/or State offices and such proposals and reports should include reasons for the abandonment; data on any former or present productive

NOTICE

The Privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et. seq., 351 et. seq., 25 U.S.C. et. seq.; 43 CFR 3160.

PRINCIPAL PURPOSE — The information is to be used to evaluate, when appropriate, approve applications, and report completion of secondary well operations, on a Federal or Indian lease.

ROUTINE USES:

or prosecutions.

- (1) Evaluate the equipment and procedures used during the proposed or completed subsequent
- (2) Request and grant approval to perform those actions covered by 43 CFR 3162.3-2(2).

 (3) Analyze future applications to drill or modify operations in light of data obtained and methods
- (4)(5) Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations
- EFFECT OF NOT PROVIDING INFORMATION Filing of this notice and report and disclosure

of the information is mandatory once an oil or gas well is drilled.

The Paperwork Reduction Act of 1980 (44 U.S.C. 3501, et. seq.) requires us to inform you that:

This information is being collected in order to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

This information will be used to report subsequent operations once work is completed and when requested, to obtain approval for subsequent operations not previously authorized.

Response to this request is mandatory for the specific types of activities specified in 43 CFR Part 3160.

BURDEN HOURS STATEMENT

Public reporting burden for this form is estimated to average 25 minutes per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management, (Alternate) Bureau Cléarance Officer, (WO-771), 18 and C Streets, N.W., Washington, D.C. 20240, and the Office of Management and Budget, Paperwork Reduction Project (1004-0135), Washington, D.C. 20503.

*U.S. GPO: 1990-773-016/06066

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT FARMINGTON RESOURCE AREA 1235 LA PLATA HIGHWAY FARMINGTON, NEW MEXICO 87401

Attachment to Notice of

Re: Permanent Abandonment

Intention to Abandon

Well: 5 Northeast Haynes

CONDITIONS OF APPROVAL

- 1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal Leases."
- 2. with the Farmington Office is to be notified at least 24 hours before the plugging operations commence (505) 326-6201.
- 3. Blowout prevention equipment is required.
- 4. The following modifications to your plugging program are to be made (when applicable):

 Plug are to be placed @ 50' below top

Mesoverle top 3935

Chacra top 3250

Pictural Cliffs top 2396

Fivitiand top 2275

Q10 Almo Base 2071

Ojo Almo Top 1470

Naciemento top. 1435

Plugs are to be a minimum of 100' +50% excess (inside casing only)
+100% excess (squeeze through perts)

See general requirenments arrached

Office Hours: 7:45 a.m. to 4:30 p.m.

GENERAL REQUIREMENTS FOR PERMANENT ABANDONMENT OF WELLS ON FEDERAL AND INDIAN LEASES FARMINGTON RESOURCE AREA

- 1. Secure prior approval either on a Sundry Notice (Form 3160-5) or verbally from the Fluids Drilling & Production Section at this office before changing the approved plugging program.
- 2. Plugging equipment used shall have separate mixing and displacement pumps and a calibrated tank to assure proper displacement of plugs. The Operator is responsible for providing all measuring devices needed to assure proper measurement of materials being used.
- 3. A proper tank or pit will be used to contain all fluids pumped from the well during plugging operations. Unattended pits are to be fenced.
- 4. All cement plugs are to be placed through tubing (or drillpipe) and shall be a minimum of 100 feet in length with 50% excess inside casing or 100% excess when plug is set in open hole or squeezed into perforations. 15.6%/gal slurry weight is to be used when using class B neat cement or when CaCl₂ is used. Use the recommended slurry weight of other type cements when they are used (Class C, Pozzolan etc.).
- 5. Any cement plugs placed when well is not full of fluid, or when well may be taking fluid, (i.e. across perfs-unless bridge plug or retainer is used, across bad csg., or fresh water formations) will be tagged (touched) after cement has set to verify proper location.
 - Sa. Testing The first plug below the surface plug shall generally be tested by either tagging the plug with the working pipe string, or pressuring to a minimum pump (surface) pressure of 1000 psig, with no more than a 10 percent drop during a 15-minute period (cased hole only). If the integrity of any other plug is questioned, it must be tested in the same manner. Also, any cement plug which is the only isolating medium for a fresh water interval or a zone containing a valuable mineral deposit should be tested by tagging with the drill string.
- 6. Mud must be placed between plugs. Plugging mud is to be made up with a minimum of 15 lbs/bbl of sodium bentonite, and a nonfermenting polymer.

 Minimum consistency of plugging mud must be 9 lbs/gal and with a minimum viscosity of 50 sec/qt. Fresh water is to be utilized for mixing mud.
- 7. Following the placement of a cement plug, the withdrawl rate for at least the length of the cement plug shall not exceed 30 ft/min, in order to minimize the contamination of the plug.

- 8. Within 30 days after plugging work is completed, file a Sundry Notice (Subsequent Report of Abandonment, Form 3160-5), in quintuplicate with Area Manager, Bureau of Land Management, 1235 La Plata Highway, Farmington, NM 87401. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.
- 9. All permanently abandoned wells are to be marked with a regulation marker (4" pipe extending 4' above the ground line) containing the information as specified in 43 CFR 3162.6(d). Unless otherwise approved.
- 10. After plugging work is completed the surface is to be rehabilitated in accord with instructions from the Fluids Surface Management Section of the Farmington Resource Area Office.

All above are minimum requirements. The period of liability under the bond of record will not be terminated until the lease is inspected and surface work approved.

Please advise this office when the well location is ready for final inspection.

Failure to comply with the above conditions of approval may result in an assessment for noncompliance and/or a Shut-in Order being issued pursuant to 43 CFR 3163.1.

You are further advised that any instructions, orders or decisions issued by the Bureau of Land Management are subject to administrative review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4 and 43 CFR 4.700.