

16-43094-2

DATA FORM 1
NOV 19 1964
YALOWPAC

RECEIVED
JUL 1 1960
OFFICE OF THE
DIRECTOR

NEW CAG 80 WAFER 1000

Original Signed
GMOI 2000

marker was installed and released, and the procedure was verbally approved by U.S.G.S. on 12-5-61.

Plug #1: 100 sxs. cement thru Gallup from 5275' to 5570'.
 Plug #2: 40 sxs. cement at top of Mesaverde from 3732' to 3850'.
 Plug #3: 80 sxs. cement thru pictured cliffs from 1864' to 2100'.
 Plug #4: 25 sxs. cement in bottom of 8-5/8" surface casing from 165' to 240'.
 Plug #5: 10 sxs. cement in top of surface casing. Install marker & abandon well.

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "staggered" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If drops or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing. Well plugged and abandoned 12-6-61. The following plugs were placed:

HISTORY OF OIL OR GAS WELL

16-48094-2 U. S. GOVERNMENT PRINTING OFFICE

FROM	TO	TOTAL FEET	FORMATION
			1. 0-100 2. 100-200 3. 200-300 4. 300-400 5. 400-500 6. 500-600 7. 600-700 8. 700-800 9. 800-900 10. 900-1000