UNITED STATES DEPARTMENT OF THE INTERIOR

•	LEASE			
	NM	23027		

	NM	230	027	
 	· 	×		

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.) 1. oil gas	8. FARM OR LEASE NAME Almagre
well well other P & A	9. WELL NO.
2. NAME OF OPERATOR Dugan Production Corp.	1 (10,) FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	S. Blanco Undes ignated PC
Box 208, Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
below.) 700' FSL _ 000' FWL	Sec 27 T24N R1W
AT SURFACE: 790 13L 2 930 1WL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	Rio Arriba NM
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 7375' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING [] MULTIPLE COMPLETE []	change on Form 9-330)
CHANGE ZONES	· <u>.</u>
ABANDON* (other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent.)	irectionally drilled give subsurface locations and
Well was plugged and abandoned as follows:	65 12
1. Spotted 36 sx cement from 3100' to 2800'	BEC 10
2. Spotted 21 sx across_stub @ 645'.	OIL COM. LIN.
3. Spotted 30 sx cement from 355' to 255'.	\ DIST. 3
4. Spotted 30' plug in top of surface pipe a	and installed dry hole marker.
5. Cleaned location. P&A	10-17-79
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED THE Petro. Eng. Thomas A Dilgan	DATE 11-21-79
(This space for Federal or State offi	APPROVED AS AMENDED
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE
Sold Harris of Manager and Man	AS ATT

Approved as to plugging of the well bore. Liability under bond is retained until surface restoration is completed.

NAROCI) estructions on Reverse Side (SGD.) MREMILIENBACH M. MILLENBACH AREA MANAGER