Budget Bureau No. 42-R358.4. Approval expires 12-31-60.

Form 9-331a (Feb. 1951)

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Offic	. 81	enta	70	
Lease No.	sp	078	532	
Unit				

SUNDRY NOTICES AND REPORTS ON WELLS

			ATER SHUT-OFF	1
NOTICE OF INTENTION TO CHANGE PLANS		i II ' '	HOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF			TERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL			E-DRILLING OR REPAIR	
MOTICE OF INTENTION TO SHOOT OR ACIDIZE			SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALIER CASING		SUPPLEMENTARY WELL HISTORY		XX
NOTICE OF INTENTION TO ABANDON WELI	L			
(INDICATE A)	BOVE BY CHECK MARI	K NATURE OF REPORT, NOTICE, OR O	THER DATA)	
(<u>_</u>			•	
			May 8,	19. 🤇
Mesa				
	1850 ft. fron	n 3000 line and 390 ft	t. from Edine of sec	25
/eli 140 is located		S I mic and war.	the of sec	**
B-SB Sec. 25	24N	7w n.x.		
(1/ Sec. and Sec. No.)	(Twp.)	(Range) (Meridia		M
Escrito-Gallup	Rio Ari	or Subdivision)	(State/or Turkler V	h + V
(Field)	(County	or suburvision)	(Salay de Tollanda, Salay de La	
he elevation of the derrick flo	or above sea le	evel is 6876 ft.	MAY15	1000
the elevation of the derries no	or above sea re			1201
	DETA	ILS OF WORK	OIL COL	OM
itate names of and expected depths to obje			· · · · · · · · · · · · · · · · · · ·	OM,
State names of and expected depths to obj	ective sands: show si		· · · · · · · · · · · · · · · · · · ·	OM, jobs, cemen
State names of and expected depths to object.	ective sands; show si ing points, and all	zes, weights, and lengths of proposother important proposed work)	od casings; indicate mudding	OM, jobs, comen
rf. Gallup @ 2 SPF f	ective sands; show si ing points, and all	izes, weights, and lengths of proposother important proposed work) 5800, 5770-5778,	ed casings; indicate mudding	AT 9
rf. Gallup @ 2 SPF f ,000# and & 43,960 g	ing points, and all rom 5788-	izes, weights, and lengths of proposother important proposed work) 5800, 5770-5778, BD 2700 pei, Av	ed casings; indicate mudding. & 5740-14. SI vg. T.P. 2900	er e
rf. Gallup @ 2 SPF f ,000# and & 43,940 g k. 3500 psi, stnd. l	ing points, and all rom 5788- rals. vtr. 1300 psi.	ses, weights, and lengths of proposother important proposed work) 5800, 5770-5778, BD 2700 pei, Avg. I.R. 42 BPI	ed casings; indicate mudding & 5740-14. Si vg. T.P. 2900 j H. Set drilla	AT 9
rf. Gallup @ 2 SPF f ,000# and & 43,960 g k. 3500 psi, stnd. l P. at 5660'. Perf @	ective sands; show aid ing points, and all large 5788-19als. wtr. 1300 pci. 2 SPF from 2 SPF from 1300 pci.	izes, weights, and lengths of proposother important proposed work) 5800, 5770-5778, BD 2700 pei, Av Avg. I.R. 42 BPI cm 5622-5596 & 55	ed casings; indicate mudding & 5740-14. Si vg. T.P. 2900 j K. Set drilla 566-44. SWF @	er e
rf. Gallup @ 2 SPF f ,000# and & 43,960 g k. 3500 psi, stnd. l P. at 5660'. Perf @	ective sands; show at ing points, and all rom 5788- jals. vtr. 300 psi. 2 SPF fre gals. vtr	zes, weights, and lengths of proposition other important proposed work) 5800, 5770-5778, BD 2700 pci, Av Avg. I.R. 42 BPI om 5622-5596 & 53 s. B.D. 1600 pci	ed casings; indicate mudding & 5740-14. Si vg. T.P. 2900 j K. Set drilla 566-44. SWF @	er e
rf. Gallup @ 2 SPF f ,000# and & 43,960 g k. 3500 psi, stnd. l P. at 5660'. Perf @	ective sands; show at ing points, and all rom 5788- jals. vtr. 300 psi. 2 SPF fre gals. vtr	izes, weights, and lengths of proposother important proposed work) 5800, 5770-5778, BD 2700 pei, Av Avg. I.R. 42 BPI cm 5622-5596 & 55	ed casings; indicate mudding & 5740-14. Si vg. T.P. 2900 j K. Set drilla 566-44. SWF @	pei, ble
rf. Gellup @ 2 SPF f ,000# and & 43,960 g k. 3500 psi, atnd. l P. at 5660'. Perf @ ,000# and. & 34,292 P. 2600 psi, atnd 14	cetive sands; show at ing points, and all rom 5788-1918. wtr. 1300 pci. 2 SPF frequence gals. wtr. 100. Avg.	See, weights, and lengths of proposition important proposed work) 5800, 5770-5778, BD 2700 pei, Av Avg. I.R. 42 BPI cm 5622-5596 a 53 B.D. 1600 pei I.R. 40.1 BPM.	ed casings; indicate mudding. 4 5740-14. Sivg. T.P. 2900 j 8. Set drillal 566-44. SWF @ 1. Nax 3000. Drilled B.P.	pei, ble
rf. Gellup © 2 SPF f ,000# and & 43,960 g k. 3500 psi, stnd. l P. at 5660'. Perf @ ,000# and. & 34,292 P. 2600 psi, stnd l4 n 186 jts of 2 3/8",	ective sands; show at ing points, and all large 5788-1218. wtr. 300 psi. 2 SPF frequence of the same state of the same	zes, weights, and lengths of proposother important proposed work) 5800, 5770-5778, BD 2700 pei, Av Avg. I.R. 42 BPI om 5622-5596 & 55 s. B.D. 1600 pei I.R. 40.1 BPM. tubing T.B. 5781	ed casings; indicate mudding. 4 5740-14. Sivg. T.P. 2900 j 8. Set drillal 566-44. SWF @ 1. Nax 3000. Drilled B.P.	pei, ble Avg.
rf. Gellup @ 2 SPF f ,000# and & 43,960 g k. 3500 psi, atnd. l P. at 5660'. Perf @ ,000# and. & 34,292 P. 2600 psi, atnd 14	ective sands; show at ing points, and all large 5788-1218. wtr. 300 psi. 2 SPF frequence of the same state of the same	zes, weights, and lengths of proposother important proposed work) 5800, 5770-5778, BD 2700 pei, Av Avg. I.R. 42 BPI om 5622-5596 & 55 s. B.D. 1600 pei I.R. 40.1 BPM. tubing T.B. 5781	ed casings; indicate mudding. 4 5740-14. Sivg. T.P. 2900 j 8. Set drillal 566-44. SWF @ 1. Nax 3000. Drilled B.P.	pei, ble Avg.
rf. Gellup © 2 SPF f ,000# and & 43,960 g k. 3500 psi, stnd. l P. at 5660'. Perf @ ,000# and. & 34,292 P. 2600 psi, stnd l4 n 186 jts of 2 3/8",	ective sands; show at ing points, and all large 5788-1218. wtr. 300 psi. 2 SPF frogals. wtr. 4.74 J.	zes, weights, and lengths of proposother important proposed work) 5800, 5770-5778, BD 2700 pei, Av Avg. I.R. 42 BPI om 5622-5596 & 55 s. B.D. 1600 pei I.R. 40.1 BPM. tubing T.B. 5781	ed casings; indicate mudding. 4 5740-14. Sivg. T.P. 2900 j 8. Set drillal 566-44. SWF @ 1. Nax 3000. Drilled B.P.	pei, ble Avg.
rf. Gallup © 2 SPF 1,000# and & 43,960 g c. 3500 psi, stnd. l P. at 5660'. Perf @ ,000# and. & 34,292 P. 2600 psi, stnd l4 n 186 jts of 2 3/8",	ective sands; show at ing points, and all large 5788-1218. wtr. 300 psi. 2 SPF frogals. wtr. 4.74 J.	zes, weights, and lengths of proposother important proposed work) 5800, 5770-5778, BD 2700 pei, Av Avg. I.R. 42 BPI om 5622-5596 & 55 s. B.D. 1600 pei I.R. 40.1 BPM. tubing T.B. 5781	ed casings; indicate mudding. 4 5740-14. Sivg. T.P. 2900 j 8. Set drillal 566-44. SWF @ 1. Nax 3000. Drilled B.P.	pei, ble Avg.
of. Gellup @ 2 SPF 1,000# and & 43,960 g c. 3500 psi, stnd. l P. at 5660'. Perf & ,000# and. & 34,292 P. 2600 psi, stnd 14 n 186 jts of 2 3/8", b. well & K.O. Rele	ective sands; show at ing points, and all large 5788-1218. wtr. 300 psi. 2 SPF frogals. wtr. 4.74 J.	zes, weights, and lengths of proposother important proposed work) 5800, 5770-5778, BD 2700 pei, Av Avg. I.R. 42 BPI om 5622-5596 & 55 s. B.D. 1600 pei I.R. 40.1 BPM. tubing T.B. 5781	ed casings; indicate mudding. 4 5740-14. Sivg. T.P. 2900 j 8. Set drillal 566-44. SWF @ 1. Nax 3000. Drilled B.P.	pei, ble Avg.
of. Gallup @ 2 SPF 1,000# and & 43,960 g c. 3500 psi, stnd. l P. at 5660'. Perf & ,000# and. & 34,292 P. 2600 psi, stnd l4 a 186 jts of 2 3/8", b. well & K.O. Rele	ective sands; show at ing points, and all large 5788-1218. wtr. 1300 psi. 2 SPF frogals. wtr. 100. Avg. 4.74 J. 1288-139	zes, weights, and lengths of proposother important proposed work) 5800, 5770-5778, BD 2700 pei, Av Avg. I.R. 42 BPI om 5622-5596 & 53 s. B.D. 1600 pei I.R. 40.1 BPM. tubing T.B. 5781 5-7-61.	ed casings; indicate midding. & 5740-14. Sivg. T.P. 2900; K. Set drilla: 566-44. SWP @ i. Nax 3000. Drilled B.P. feet set at 5	pei, ble Avg. A
rf. Gallup © 2 SPF 1,000# and & 43,960 g c. 3500 psi, stnd. l P. at 5660'. Perf @ ,000# and. & 34,292 P. 2600 psi, stnd l4 n 186 jts of 2 3/8",	ective sands; show at ing points, and all large 5788-1218. wtr. 1300 psi. 2 SPF frogals. wtr. 100. Avg. 4.74 J. 1288-139	zes, weights, and lengths of proposother important proposed work) 5800, 5770-5778, BD 2700 pei, Av Avg. I.R. 42 BPI om 5622-5596 & 53 s. B.D. 1600 pei I.R. 40.1 BPM. tubing T.B. 5781 5-7-61.	ed casings; indicate midding. & 5740-14. Sivg. T.P. 2900; K. Set drilla: 566-44. SWP @ i. Nax 3000. Drilled B.P. feet set at 5	pei, ble Avg. A
of. Gallup © 2 SPF 1 OOOH and & 43,960 g 3500 psi, stnd. l A 5660'. Perf & OOOH and. & 34,292 Called Str. of 2 3/8". Owell & K.O. Rele Tunderstand that this plan of work mu Val R. Reese	ective sands; show at ing points, and all large 5788-1918. Wtr. 1300 pci. 2 SPF frogals. Wtr. 1400. Avg. 14.74 J. 14.866 rig	zes, weights, and lengths of proposition important proposed work) 5800, 5770-5778, BD 2700 pei, Av Avg. I.R. 42 BPI cm 5622-5596 a 53 B.D. 1600 pei I.R. 40.1 BPM. tubing T.B. 5781 5-7-61.	ed casings; indicate midding. & 5740-14. Sivg. T.P. 2900; K. Set drilla: 566-44. SWP @ i. Nax 3000. Drilled B.P. feet set at 5	pei, ble Avg. A
of. Gallup @ 2 SPF 1 OOO# and & 43,960 g at 5660'. Perf & OOO# and. & 34,292 2 2600 psi, stnd 14 a 186 jts of 2 3/8", b. well & K.O. Rele Tunderstand that this plan of work mu Val R. Reese	ective sands; show at ing points, and all irom 5788-1918. Vtr. 1300 psi. 1300 psi. 1300 psi. 1300 psi. 1400. Avg. 1400. Avg. 1400. Avg. 1500. Avg. 1600. A	zes, weights, and lengths of proposition important proposed work) 5800, 5770-5778, BD 2700 pei, Av Avg. I.R. 42 BPI cm 5622-5596 a 53 B.D. 1600 pei I.R. 40.1 BPM. tubing T.B. 5781 5-7-61.	ed casings; indicate midding. & 5740-14. Sivg. T.P. 2900; K. Set drilla: 566-44. SWP @ i. Nax 3000. Drilled B.P. feet set at 5	pei, ble Avg. A
of. Gallup @ 2 SPF 1 OOO# and & 43,960 g at 5660'. Perf & OOO# and. & 34,292 2 2600 psi, stnd 14 a 186 jts of 2 3/8", b. well & K.O. Rele Tunderstand that this plan of work mu Val R. Reese	ective sands; show at ing points, and all irom 5788-1918. Vtr. 1300 psi. 1300 psi. 1300 psi. 1300 psi. 1400. Avg. 1400. Avg. 1400. Avg. 1500. Avg. 1600. A	zes, weights, and lengths of proposition important proposed work) 5800, 5770-5778, BD 2700 pei, Av Avg. I.R. 42 BPI cm 5622-5596 a 53 B.D. 1600 pei I.R. 40.1 BPM. tubing T.B. 5781 5-7-61.	ed casings; indicate midding. & 5740-14. Sivg. T.P. 2900; K. Set drilla: 566-44. SWP @ i. Nax 3000. Drilled B.P. feet set at 5	pei, ble Avg. A
cf. Gallup @ 2 SPF 1 ,000# and & 43,960 g c. 3500 psi, stnd. l P. at 5660'. Perf & ,000# and. & 34,292 P. 2600 psi, stnd l4 a 186 jts of 2 3/8", b. well & K.O. Rele Tunderstand that this plan of work mu Val R. Resse address Lobby, Simms E	ective sands; show at ing points, and all large 5788-1918. Wtr. 1300 psi. 2 SPF frogals. Wtr. 1300. Avg. 4.74 J. 1918-1918. Associate & Associated Ruilding	zes, weights, and lengths of proposother important proposed work) 5800, 5770-5778, BD 2700 pci, Av Avg. I.R. 42 BPI om 5622-5596 & 53 B.D. 1600 pci I.R. 40.1 BPM. tubing T.B. 5781 5-7-61.	ed casings; indicate midding. & 5740-14. Sig. rg. T.P. 2900; R. Set drilla: 566-44. SWP @ i. Nax 3000. Drilled B.P. feet set at 5: before operations may be com	pei, ble Avg. h 789 fo
of. Gallup @ 2 SPF 1 OOO# and & 43,960 g at 5660'. Perf & OOO# and. & 34,292 2 2600 psi, stnd 14 a 186 jts of 2 3/8", b. well & K.O. Rele Tunderstand that this plan of work mu Val R. Reese	ective sands; show at ing points, and all large 5788-1918. Wtr. 1300 psi. 2 SPF frogals. Wtr. 1300. Avg. 4.74 J. 1918-1918. Associate & Associated Ruilding	zes, weights, and lengths of proposother important proposed work) 5800, 5770-5778, BD 2700 pci, Av Avg. I.R. 42 BPI om 5622-5596 & 53 B.D. 1600 pci I.R. 40.1 BPM. tubing T.B. 5781 5-7-61.	ed casings; indicate midding. & 5740-14. Sig. rg. T.P. 2900; R. Set drilla: 566-44. SWP @ i. Nax 3000. Drilled B.P. feet set at 5: before operations may be com	pei, ble Avg. h 789 fo
cf. Gallup @ 2 SPF 1 ,000# and & 43,960 g c. 3500 psi, stnd. l P. at 5660'. Perf & ,000# and. & 34,292 P. 2600 psi, stnd l4 a 186 jts of 2 3/8", b. well & K.O. Rele Tunderstand that this plan of work mu Val R. Resse address Lobby, Simms E	ective sands; show at ing points, and all large 5788-1918. Wtr. 1300 psi. 2 SPF frogals. Wtr. 1300. Avg. 4.74 J. 1918-1918. Associate & Associated Ruilding	zes, weights, and lengths of proposition important proposed work) 5800, 5770-5778, RD 2700 pci, Av Avg. I.R. 42 BPI om 5622-5596 & 5: B.D. 1600 pci I.R. 40.1 BPM. tubing T.B. 5781 5-7-61. n writing by the Geological Survey ates, Inc. Crigin By MORR	od casings; indicate mudding. & 5740-14. Sive. vg. T.P. 2900 K. Set drilla 566-44. SWP @ i. Nax 3000. Drilled B.P. feet set at 5	pei, ble Avg. h 789 fo