U.S.G.S. Farmington
Robert Ramirez

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.
SF-080202-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL [X] GAS WELL [ ] OTHER

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR
BCO, Inc.

8. FARM OR LEASE NAME
Federal 4-26

3. ADDRESS OF OPERATOR
135 Grant Ave. Santa Fe, New Mexico 87501

9. WELL NO.
1

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
1850' FNL and 1700' FEL Sec 26 T24N R7W

10. FIELD AND POOL, OR WILDCAT
Escrito Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
26 T24N R7W NMPM

RECEIVED
MAR 1 1983
GEOLOGICAL SURVEY

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
GR 6712

12. COUNTY OR PARISH
Rio Arriba

13. STATE
N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]
REPAIR WELL	XXX	CHANGE PLANS	[ ]
(Other)			

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	[ ]	REPAIRING WELL	[ ]
FRACTURE TREATMENT	[ ]	ALTERING CASING	[ ]
SHOOTING OR ACIDIZING	[ ]	ABANDONMENT*	[ ]
(Other)			

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Believe well has casing failure. Intend to set RBP above Gallup perfs (5417-5494) and then use packer to find the hole in the casing. Intend to repair said hole with cement, let cement set for at least 72 hours, then drill out cement, remove RBP, swab well and place back in production.

RECEIVED

APPROVED

18. I hereby certify that the foregoing is true and correct

SIGNED [signature] TITLE Office Manager DATE 3/10/83

(This space for Federal or State office use)

JAMES F. SIMS
DISTRICT ENGINEER

APPROVED BY ________ TITLE ________ DATE ________
CONDITIONS OF APPROVAL, IF ANY:

NMOCC