

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool South Blance Formation Pictured Cliffs County Rio Arriba
Initial - Annual - Special X Date of Test 1/6/58
Company Magnolia Petroleum Company Lease J. F. Brown Well No. 1
Unit C Sec. 27 Twp. 24N Rge. 2W Purchaser Pacific Northwest
Casing 5 1/2" Wt. 11.4 I.D. 5.012" Set at 3265' Perf. 3148' To 3213'
Tubing 2 3/8" Wt. 4.74 I.D. 1.995 Set at 3154' Perf. - To -
Gas Pay: From 3148' To 3213' L - xG Est. 0.680 GL - Bar. Press. 12 psi
Producing Thru: Casing - Tubing X Type Well Single - G
Single-Bradenhead-G. G. or G.O. Dual
Date of Completion: 9/24/56 Packer None Reservoir Temp. -

OBSERVED DATA

Tested Through (Pressure) (Choke) (Meter) Type Taps -

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Line) Size	(Choke) (Restriction) Size	Press. psig	Diff. h_w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						890	-	893		
1.	2"	0.750	87	-	56	87	56	842	-	3 hrs.
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F_t	Gravity Factor F_g	Compress. Factor F_{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12.3650	-	99	1.0039	.9393	-	1.154
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS


Gas Liquid Hydrocarbon Ratio - cf/bbl.
Gravity of Liquid Hydrocarbons - deg.
 P_c - (1-e^{-s})
Specific Gravity Separator Gas -
Specific Gravity Flowing Fluid -
 P_c 902 P_c^2 813.6

No.	P_w P_w (psia)	P_t^2	$F_c Q$	$(F_c Q)^2$	$(F_c Q)^2$ (1-e ^{-s})	P_w^2	$P_c^2 - P_w^2$	Cal. P_w	$\frac{P_w}{P_c}$
1.	254	-	-	-	-	64.5	749.1		
2.									
3.									
4.									
5.									

Absolute Potential: 1238 MCFPD; n 0.85

COMPANY MAGNOLIA PETROLEUM COMPANY
ADDRESS P. O. BOX, 2406, HOHRS, NEW MEXICO
AGENT and TITLE Blaise H. Hays, Gas Engineer
WITNESSED -
COMPANY -

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressability factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .

OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. 1000	3	
DATE		
TIME		
BY		
REMARKS		
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
51		
52		
53		
54		
55		
56		
57		
58		
59		
60		
61		
62		
63		
64		
65		
66		
67		
68		
69		
70		
71		
72		
73		
74		
75		
76		
77		
78		
79		
80		
81		
82		
83		
84		
85		
86		
87		
88		
89		
90		
91		
92		
93		
94		
95		
96		
97		
98		
99		
100		