## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Poo]	South B	lanco		_Formation	n_Piet	are Cli	ff	County	Rio Ar	ribba
	ial_X									
	pany E. B									
	, <u>M</u> s									
	ng 7" W									
	ng 1.315 W									
										38
	ucing Thru:									38•
						9 i r	പരിചെയ്യാർ	anhand C (	~ ~~ C	O. Dual
Dage	of Complet	1011	<u> </u>	Packe			neserv	olr Temp		
<b>.</b> .		TYTY	,			ED DATA				
Test	ed Through	(Freve	(Chok	e) ( <del>Meter)</del>	<b>.</b>			Type Taps	5	,
	(Prover)		ow Data	Dice	m	Tubing		Casing Da		
No.	(Line)	(ATOEL	ا سئس	ss. Diff.	Temp.	Press.	Temp.	Press.	Temp.	Duration of Flow
	Size	Size	e ps:	ig h <sub>w</sub>	°F.	psig	°F.	psig	°F. ∣	Hr.
SI		7/10				602		602		7 Day shat:
1. 2.		3/4"		9	50	51	60	39	60	5 Hours.
3.		···					<del> </del>			
<u>4.</u> 5.										
<u> 5. !</u>							<u> </u>			
		<del></del>				CULATION				
No.	Coefficie	ent		Pressure		Temp.	•		1	ate of Flow
	(24-Hou	c) 7/	hwpf	psia	· F		Factor F <sub>g</sub>	Factor F <sub>pv</sub>		Q-MCFPD 15.025 psia
1.	12,365		4. T	51	1.00		.9759	1.010		622
1. 2. 3. 4. 5.										
3.										
5.							<del></del>			
ravit	iquid Hydroc y of Liquic	l Hydroc	arbons		cf/bbl.		Speci	fic Gravit fic Gravit <b>614</b>		
<b>-</b> T	P <sub>w</sub>						<del></del>	0 -	<u> </u>	<del>                                     </del>
No.	Pt (psia)	$P_{\mathbf{t}}^{2}$	F <sub>c</sub> Q	$(F_cQ)^2$	(F	cQ) <sup>2</sup> -e <sup>-s</sup> )	$P_{\mathbf{w}}^2$	$P_c^2 - P_w^2$	Cal P <sub>w</sub>	, <del>,</del>
<u> 1.                                   </u>					<u> </u>		3.72	373.27	- W	
1. 2. 3.										
4.1			<b></b>	+		<del></del>			<del></del>	1
4. 5.										
Absol	ute Potenti	al:	627		MCFPD;	n .85				
COMPA	NY		Well P	rodus \$1 of	1 Co.				$-\mathcal{N}$	11/1
ADDRE	SS and TITLE	<del></del>	Owner	ani Driv	Fa	rmingto	n, New	Marigo	/191	11 lery
WITNE			*******	<del></del>	<del></del>		1 A	<b>*</b>		
COMPA							Of No	V. VI		
				. <u></u>	REM	ARKS	, co	18/1		
							( ox	188		

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q  $\equiv$  Actual rate of flow at end of flow period at W. H. working pressure (P<sub>W</sub>). MCF/da. @ 15.025 psia and 60° F.
- $P_c$  72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw- Differential meter pressure, inches water.
- Fg Gravity correction factor.
- $F_t$  Flowing temperature correction factor.
- F<sub>DV</sub>- Supercompressability factor.
- n \_ \_ Slope of back pressure curve.

Note: If  $P_{\rm W}$  cannot be taken because of manner of completion or condition of well, then  $P_{\rm W}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\rm t}$ .

OIL CONSERVAT	ION COMMI	SSION						
AZTEC DISTRICT OFFICE								
No. Copies Received 3								
Dillin								
		1						
Operator	The second second	<u>.</u> 1						
Sente 2	7							
Projection (17)	on the second of the second	, <del>-</del>						
State Land Only								
U. S. G. S.								
Transporter								
File	j	es a mari						