For (F	m el	7	316	Þ	<b>)</b> [	ROVED
				J	<u>U).</u>	3 () 1956
			A C T	JE NG	R.B.\ 9 · s	W. LONG DEP
			'			

(SUBMIT IN TRIPLICATE)

## UNITED STATES ARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Serta Pe	
Lease No	076909	
Unit	Lindrith	Unit

SUNDRY	NOTICES A	ND REPORTS	
OTICE OF INTENTION TO DRILL			WATER SHUT-OFF
OTICE OF INTENTION TO CHANGE			SHOOTING OR ACIDIZING
OTICE OF INTENTION TO TEST W	ATER SHUT-OFF		ALTERING CASING
OTICE OF INTENTION TO RE-DRIE	LL OR REPAIR WELL		RE-DRILLING OR REPAIR
OTICE OF INTENTION TO SHOOT			ABANDONMENT
IOTICE OF INTENTION TO PULL O	1	SUPPLEMENTARY WELL HI	STORY
OTICE OF INTENTION TO ABANDO	ON WELL		
(IND	ICATE ABOVE BY CHECK MARK	NATURE OF REPORT, NOTICE, OR	OTHER DATA)
			July 25,, 195
			1/3
			ft. from W line of sec. 21
Section 21 (1/4 Sec. and Sec. No.)	er ray	(Range) (Meric	dian)
wildcat		ribe	Her Maxico
(Field)	(County o	or Subdivision)	(State or Territory)
ne elevation of the derri			
The elevation of the derri	DETA	ILS OF WORK	posed casings; indicate mudding jobs, cem
	DETAIns to objective sands; show sizing points, and all of the 3120°.  2", 15.50%, J-55  CHEST, 75 SACKS	casing (3170°) series, 45 cel.	
6-4-56. Total Day R n 97 joints 5 1/2 75 sacks regular of Held 1000; for 30 to	DETAIns to objective sands; show sizing points, and all of the sands; show size the sands; sh	Casing (3170') sering	t at 3180° with
6-4-56. Total Day R.n. 97 joints 5 1/2 75 sacks regular of Held 1000; for 30 to Top of coment by to	DETAIns to objective sands; show sizing points, and all of the 3120°. 2°, 15.50°, J-55 cment, 75 sacks consults.  Supersture survey work must receive approval in turns.	casing (3170°) serial s	t at 3180° with
ate names of and expected depth  6-1-56. Total Dep  R n 97 joints 5 1/2  75 sacks regular co  Held 1000 for 30 1  Top of coment by to  Junderstand that this plan of  company El Paso Re  ddress Box 997	DETAIns to objective sands; show sizing points, and all of the 3120°. 2°, 15.50°, J-55 cment, 75 sacks consults.  Supersture survey work must receive approval in turns.	casing (3170°) serial s	t at 3180° with