

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.
Form Approved.

Land Office **Santa Fe**
Lease No. **03992**
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 13, 1963

SUNICO-FEDERAL

Well No. **17** is located **1830** ft. from **XXX** line and **1830** ft. from **XXX** line of sec. **23**

SW/4 Section 23 **24 North 2 West** **101PM**

(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Civilian **Eliz Arriba** **New Mexico**

(Field) (County or Subdivision) (State or Territory)



The elevation of the ~~surface~~ **ground** floor above sea level is **7239** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

To supplement report of 1-14-63, subject well was perforated at 3204-3214. Frac treated down casing with 30,000 sand and 36,000 gallons water. Breakdown pressure 2800 psi. Treating pressure 2200-2400 psi. Instant shut-in pressure 280 psi. Injection rate 44 BPM. Stuffed well in. Ran 1 1/4" tubing to 3184 feet.

Presently awaiting testing.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

E. L. Funderland
Company _____
Address **1402 Denver U. S. National Center**
Denver 2, Colorado

By *E. L. Funderland*
Title *mgr*