Form	3160	- 5
(Nove	mber	1983)
Worm	PLV	a=331\

UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions a reverse side)

2109 pageout-man
Expires August 21, 1985
Budget Bureau No. 1004-013
r orm approved.

١,	LEASE	DESIGNATION	AND	BERIAL	NO

BUREAU	OF	LAND	MAN	IAGE™	į :,

CHRIDDY	MOTICES	A ND	REPORTS	ON	WFI	1
ZIINIJK Y	NUMBER	AINII	REPURS		VVEL	

6. IF INDIAN ALLOTTEE OR TRIBE NAME

	(Do not use this for	rm for proposals to drill or to deepen or blug back to a different reservoi	
1.	OIL GAS WELL Y	OTHER	7. UNIT AGREEMENT NAME
2.	NAME OF OPERATOR		8. FARM OR LEASE NAME
	E. L. Fundings	land	Sunical Federal
3.	ADDRESS OF OPERATOR	land	9. WELL NO.
	7/00 Orchard P	oad, Suite 240 Englewood, Colorado 80111	17
ā.	LOCATION OF WELL (Repo	ort location clearly and in accordance with any State requirements.*	10. FIELD AND POOL, OR WILDCAT
	See also space 17 below. At surface)	Gavalin PC
		1850' FSL & 1850' FWL	11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA
14.	PERMIT NO.	15. ELEVATIONS (Show whether 14, 87, GR, etc.)	Sec. 23, T24N, R2W
		7259 GR	Rio Arriba NM
16.		Check Appropriate Box To Indicate Sature of Notice, Repo	er or Other Data
	NOT	MCE OF INTENTION TO:	. BSEQUENT REPORT OF:
	TEST WATER SHUT-OFF	PULL OR ALTER CASING WATER SHUT-OFF	REPAIRING WELL
	FRACTURE TREAT	MULTIPLE COMPLETE FRACTURE TREATME	ALTERING CASING
	SHOOT OR ACIDIZE	ABANDON* SHOOTING OR ACIDIS	ABANDONMENT* X
	REPAIR WELL	CHANGE PLANS (Other)	
	(Other)	(Note: Repor	t sults of multiple completion on Well is completion Report and Log form.)
17.	proposed work. If we nent to this work.) *	OMPLETED OPERATIONS (Clearly state all performs details, and give pertine ell is directionally drilled, give subsurfact operations and measured and tri	nt sates, including estimated date of starting any ertical depths for all markers and zones perti-
	Tune 28 1988	Moved Welltech to location. Could not get o	on location due to mud.
	Tuly 5 1988	Rigged up rig. Installed BOP. Tallied 2-3/8	" tubing and ran in hole
	July 3, 1900	to 3260'. Circulated hole into rig pit. Cem	mented from 3260' to 1230'
		with 175 sacks (206.50 cu. ft.) Class B Nea	it cement. Pulled tubing
		and shut down.	it coment, luited tooting
		and shut down.	1 10001 0 1

July 6, 1988 Ran in hole with tubing and tagged cement plug at 1230'. Cemented from 1230' to surface with 100 sacks (118 cu. ft.) Class B Neat cement. Remove BOP. Squeezed braiden head annulus with 35 sacks (41.93 cu. ft.) Class B Neat cement to 1500 psi. Cut off wellhead. Installed dry hole marker. Cut off guywire anchors. Cut out flowlines.

Approved as to pluggion of th Liability county constitutionals. surface restoration is eampioud.

()					4
18. I hereby certify that the coreging is true and correct SIGNED	Tin Lin	Agent		DATE July 8,	1988
(This space for Federal or State office use)	SALEL.			_	
APPROVED BYCONDITIONS OF APPROVAL. IF ANY:	TITLE		Jan	ne C. Al	vari
			77	M	

*See Instruction