Form 3360 (November (Formerly	1983) OCCAPITATION OF THE INTERIOR (Other Interiors of	SF - 078562	
(Do	SUNDRY NOTICES AND REPORTS ON WELLS not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use TAPPLICATION FOR PERMIT— for such perspecials.	6. DE INDIAN, ALLOTTER OR TRUSC NAME	
ī.	WELL OTHER	T. ORIT AGREEMENT NAME	
	, Inc.	Lybrook	
•• •••	Grant Avenue, Santa Fe, New Mexico 87501	9. WELL EO. #6	
1. LOCATIO	s or well (Report location clearly and in accordance with any State requirements.* space 17 below.)	10. FIRED AND FOOL, OR WILDGET	
2300	RECEIVED	Escrito Gallun 5 to 6M	
14. PERMIT	DEC 1 6 1986	Sec. 22 - 24N - 7W	
14. 744.211	6804 GR BUREAU OF LAND MANAGEM	Rio Arriba N.M.	
16.	Check Appropriate Box To Indicate Nature of Notice, Report,		
	FOTICE OF INTENTION TO:	MARQUENT EMPORT OF:	
IIST W	ATER SHUT-OFF PULL OR ACTER CASING WATER SHUT-OFF	grpateing well X	
·	RE ACIDIZE ABANDON* PRACTICE TERATMENT	ALTERING CARING	
EEPAIK	WELL CHANGE PLANS (Other)		
(Other)	(Note: Report re Completion or Rec	salts of maltiple completion on Well completion Report and Log form.)	
1-19-86	Bridgeplug set at 5348. Dropped 10 gallons of sand on	top of bridgeplug.	
1-24-86	Located holes between 518' and 550' and between 2033' and Pruitt at B.L.M. at 6:20 p.m. we planned to cement 11-25	-86.	
1-25-86	Set EZ-drill cement retainer at 1906'. Cemented with 1 with 2% CACL mixed to yield 1.18 barrels per sack, with 7 Final squeeze pressure 1200 #s. Reversed out 27 barrels, at 266'. Cemented with 180 sacks Class H cement with 2% barrels. Circulated cement to surface. Closed bradenhea at 800 #s pressure. Held 700 #s pressure at end of job w	.4 barrels displacement. no cement. Set packer CACL mixed to yield 1.18 d valve. Squeezed 3 barrels	
1-26-86	Tagged cement 357' from surface. Drilled good cement through 524' then fell through. Tagged retainer at 1906', drilled 35 minutes and retainer fell down hole to 1937'. Came out of hole and discovered a cone missing from bit.		
2-1-86	Fished out cement retainer and cone with globe basket. W drilled to 1967'.	ent in with bit and	
2-2-86	Drilled good cement from 1967'. Fell through at 2055'. Pressure tested with 200 #s at surface. Held for 30 minut	Drilled stringers to 2064'. tes.	
18. I bereby o	ertify that the foregoing is true and correct		
SIGNED _	Chabell 13. Meshan TITLE Comptroller	12- 5 -86 ·	
APPROVE			
COMOLITE		temminatur nessounce mitel	
	See Instruction Perene Sile 1. 3	· SMN	
	MMJW.		

operator: BCO, Inc.

135 Grant

Santa Fe, NM 87501

SUNDRY NOTICES AND REPORTS ON WELLS

Lease Name: Lybrook Well No.: 6

Field: Escrito Gallup 5 to 6M

Section 22, T24N, R7W

Rio Arriba, NM

PAGE TWO

2-3-86	Rolled hole with KCL. Cleaned out sand on top of bridgeplug. with bridgeplug. Landed well at 5632'. Swabbed well.	Came out of hole
2-4-86	Swabbed well.	

2-6-86 Placed well back in production.

Swabbed well.

2-5-86